Revision: 16.04.2022

Printing date 29.01.2024

Version number 3.2

1 Identification

- · Product identifier
- · Trade name: ANTIRUST SPRAY
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Anticorrosion additive Only for proper handling.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG Bern-Zürich-Strasse 31, Postfach CH-4901 Langenthal Tel. +41 (0)62 919 75 75 www.motorex.com

A1 Accessory Imports 60-62 Burchill St. Loganholme 4129 QLD Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol.

Pressurised container: May burst if

heated.

Serious eye damage/irritation - Category 2A H319 Causes serious eve irritation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters

airways.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms







GHS02 GHS07

· Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Distillates (petroleum), hydrotreated light paraffinic

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

(Contd. on page 2)

MOTOREX*
Oil of Switzerland

Printing date 29.01.2024 Version number 3.2 Revision: 16.04.2022

Trade name: ANTIRUST SPRAY

(Contd. of page 1)

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	25-50%
EC number: 918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304	10-25%
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	≥10-<20%
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1, H304	10-25%
EC number: 919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	5-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6	butan-1-ol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.5%

· Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons ≥30%

· Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Remove residues with soap and water.

(Contd. on page 3)

MOTOREX*
Oil of Switzerland
Revision: 16.04.2022

Printing date 29.01.2024 Version number 3.2

Trade name: ANTIRUST SPRAY

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- · Storage class: 2 B
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

(Contd. on page 4)

MOTOREX Oil of Switzerland
Revision: 16.04.2022

Printing date 29.01.2024

Version number 3.2

Trade name: ANTIRUST SPRAY

		rina at the w	orknlace:	
	its with limit values that require monito butane, pure	ing at the w	or aprace.	
	WES Long-term value: 1900 mg/m³, 800 ppm			
	4-98-6 propane			
WES Asp				
71-36-3 b				
WES Pea	ak limitation: 152 mg/m³, 50 ppm			
Sk	,			
DNELs				
Hydrocar	bons, C9-C11, n-alkanes, isoalkanes, c	ycloalkanes,	<2% aromatics	
Oral	DNEL/general population/Systemic effect	ts/Long-term	300 mg/kg/24h (consumer)	
Dermal	DNEL / Workers / Systemic effects / Long	g-term	300 mg/kg/24h (worker)	
	DNEL/general population/Systemic effect	ts/Long-term	300 mg/kg/24h (consumer)	
Inhalative	DNEL / Workers / Systemic effects / Long	g-term	1,500 mg/m3 (worker)	
	DNEL/general population/Systemic effect	ts/Long-term	900 mg/m3 (consumer)	
64742-55	8 Distillates (petroleum), hydrotreated		nic	
Dermal	DNEL / Workers / Local Effects / Long-te	rm	1 mg/kg/8h (worker)	
Inhalative	DNEL		2.7-5.4 mg/m3/8h (worker)	
	DNEL		1.2 mg/m3/24h (consumer)	
	bons, C9-C12, n-alkanes, isoalkanes, c			
Oral	DNEL/general population/Systemic effect	•	,	
Dermal	DNEL / Workers / Systemic effects / Long-term		44 mg/kg/24h (worker)	
	DNEL/general population/Systemic effects/Long-term		, ,	
	DNEL/general population/Systemic effect	ts/Long-term	71 mg/m3 (consumer)	
71-36-3 b				
Oral	DNEL/general population/Systemic effect			
Inhalative	DNEL / Workers / Local Effects / Long-te		310 mg/m3 (worker) 55 mg/m3 (consumer)	
	DNEL/general population/Local effects/Lo	eneral population/Local effects/Long-term		
PNECs				
	-8 Distillates (petroleum), hydrotreated			
Oral PNE	C / Predators / Secondary poisoning	9.33 mg/kg (predators))	g food (secondary poisoni	
71-36-3 b				
			aquatic organisms)	
PNEC / Aquatic organisms / Marine water		_	(aquatic organisms)	
PNEC/Aquatic org/intermittent 2 releases(freshwater)				
PNEC/Aquatic organisms/Sewage treatment 2,476 mg/l (aquatiplant/STP				
PNEC / Aquatic organisms / Sediment 0.178 mg/kg (aquatic organisms) (freshwater)				
PNEC / Aquatic organisms / Sediment 0.0178 mg/kg (aquatic organisms) (marine water)				
PNE	C / Terrestrial organism / Soil	0.015 mg/kg	(terrestrial organisms)	

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

(Contd. on page 5)

MOTOREX Oil of Switzerland

Printing date 29.01.2024 Version number 3.2 Revision: 16.04.2022

Trade name: ANTIRUST SPRAY

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Not required.
- · Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Liquefied gas
Colour: Black
Odour: Solvent-like
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: <-10 °C

Flammability (solid, gas):
 Decomposition temperature:
 Not applicable.
 Not determined.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

Explosion limits:

Lower: 0.5 Vol %
Upper: 8.5 Vol %
Vapour pressure: Not determined.

Density at 20 °C: 0.709 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

Viscosity:

· **Dynamic:** Not determined.

• Kinematic: < 1 mm²/s @40 °C (DIN 51562-1)</p>

(Contd. on page 6)

Revision: 16.04.2022

Printing date 29.01.2024

Version number 3.2

Trade name: ANTIRUST SPRAY

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

LD/LC50 values relevant for classification:

· Acute toxicity Based on available data, the classification criteria are not met.

	butane, pure	1,442.738-1.443 mg/l (rat)
IIIIaialive	LC50 / 15 min	
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	LC50 / 4h	658 mg/l (rat)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.2-21.4 mg/l (rat)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)
Hydrocar		n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
Oral	LD50	5,000-15,000 mg/kg (rat)
Orar	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
<i></i>		3,160-5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)
	LC50 / 8h	41-4,467 ppm (rat)
	LC50 / 8h	5 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m3 (rat)
64742-55-	·8 Distillates (p	etroleum), hydrotreated light paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
		(Contd. on pag

MOTOREX Oil of Switzerland
Revision: 16.04.2022

Printing date 29.01.2024

Version number 3.2

Trade name: ANTIRUST SPRAY

			(Contd. of page 6)
	NOAEL	980 mg/m3 (rat)	
Hydrocar	bons, C9-C12,	n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Oral	LD50	15,000 mg/kg (rat)	
Dermal	LD50	4 ml/kg (rat)	
	NOAEL	495 mg/kg/24h (rat)	
Inhalative	LC50 / 4h	13.1 mg/l (rat)	
	NOAEL	300 ppm (rat)	
	NOAEC	690 ppm (rat)	
	LOAEC	100-1,293 ppm (rat)	
71-36-3 b	utan-1-ol		
Oral	LD50	2,292 mg/kg (rat)	
	LD50	2.83 ml/kg (rat)	
	NOEL	125 mg/kg/24h (rat)	
	LOEL	500 mg/kg/24h (rat)	
Dermal	LD50	4.24 ml/kg (rabbit)	
	LD50	3,430 mg/kg (rabbit)	
Inhalative	LC50 / 4h	17.76 mg/l (rat)	
	NOEL	500 ppm (rat)	

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

12 Ecological Information

·Toxicity

TOXION	
· Aquatic	toxicity:
106-97-	8 butane, pure
LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
Hydroca	arbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
LL50	1,000 mg/l/96h (fish)
LL50	1,000 mg/l/72h (fish)
LL50	1,000 mg/l/48h (fish)
LL50	1,000 mg/l/24h (fish)
LL0	100 mg/l/96h (fish)
EL50	1,000 mg/l/48h (aquatic invertebrates)
EL50	1,000 mg/l/24h (aquatic invertebrates)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
NOELR	0.131 mg/l/28d (fish)
NOELR	0.23 mg/l/21d (aquatic invertebrates)
	(Contd. on page 8)

(Contd. on page 8)

Revision: 16.04.2022

Printing date 29.01.2024

Version number 3.2

Trade name: ANTIRUST SPRAY

		(Contd. of page
	3-100 mg/l/72h (algae / cyanobacteria)	
	5-8 Distillates (petroleum), hydrotreated light paraffinic	
LL50	10,000 mg/l/96h (aquatic invertebrates)	
	100 mg/l/96h (fish)	
	>100 mg/l/96h (Pimephales promelas) (OECD 203)	
LL50	10,000 mg/l/72h (aquatic invertebrates)	
LL50	10,000 mg/l/48h (aquatic invertebrates)	
EL50	10,000 mg/l/48h (aquatic invertebrates)	
NOEL	>100 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201)	
Hydroca	arbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
EC10	0.109-0.248 mg/l/21d (aquatic invertebrates)	
EC50	0.58-1.2 mg/l/96h (algae / cyanobacteria)	
EC50	0.53-0.94 mg/l/72h (algae / cyanobacteria)	
EC50	0.328-0.423 mg/l/21d (aquatic invertebrates)	
LL50	10-30 mg/l/96h (fish)	
LL50	10-30 mg/l/72h (fish)	
LL50	10-30 mg/l/48h (fish)	
LL50	30-100 mg/l/24h (fish)	
EL50	2.5-5.5 mg/l/96h (algae / cyanobacteria)	
EL50	10-22 mg/l/48h (aquatic invertebrates)	
EL50	22-46 mg/l/24h (aquatic invertebrates)	
NOEC	0.097-0.372 mg/l/21d (aquatic invertebrates)	
NOEC	0.16 mg/l/72h (algae / cyanobacteria)	
NOEC	0.16 mg/l/96h (algae / cyanobacteria)	
NOELR	0.13 mg/l/28d (fish)	
NOELR	0.28-1.4 mg/l/21d (aquatic invertebrates)	
	0.3 mg/l/96h (fish)	
LOEC	0.203-0.833 mg/kg/28d (aquatic invertebrates)	
71-36-3	butan-1-ol	
LC50	1,376 mg/l/96h (fish)	
EC50	225 mg/l/96h (algae / cyanobacteria)	
EC50	18 mg/l/21d (aquatic invertebrates)	
EC50	1,328 mg/l/48h (aquatic invertebrates)	
NOEC	4.1 mg/l/21d (aquatic invertebrates)	
NOEC	519 mg/l/96h (fish)	
NOEC	415 mg/l/48h (aquatic invertebrates)	

- · Persistence and degradability No further relevant information available. · Behaviour in environmental systems:

· Bioaccumulative	· Bioaccumulative potential		
106-97-8 butane,	106-97-8 butane, pure		
Partition coefficien	Partition coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)		
Hydrocarbons, C	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Biodegradability	80 % (28d) (Bioaccumulation) (OECD 301 F)		
64742-55-8 Distillates (petroleum), hydrotreated light paraffinic			
Partition coefficien	t >3.5 [] (log Kow) (Bioaccumulation)		
	(Contd. on page		

(Contd. on page 9)

Revision: 16.04.2022

Printing date 29.01.2024 Version number 3.2

Trade name: ANTIRUST SPRAY

		(Contd. of page 8)
Hydrocarbons, C9	-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Biodegradability	74.7 % (28d) (Biodegradability) (OECD 301 F)	
71-36-3 butan-1-ol		
Partition coefficient	1 [] (log Kow) (Bioaccumulation)	
Biodegradability	>70 % (28d) (Biodegradability) (OECD 301 A)	

- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

7/I I PO PO	nort in	formation

· UN-Number · ADG, IMDG, IATA	UN1950	
UN proper shipping name		
· ADG	1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	

- · Transport hazard class(es)
- · ADG



2 5F Gases. · Class 2.1

· Label

(Contd. on page 10)

Revision: 16.04.2022

Printing date 29.01.2024 Version number 3.2

Trade name: ANTIRUST SPRAY

(Contd. of page 9)

· IMDG, IATA



2.1 Gases. · Class 2.1

· Label

· Packing group

· ADG, IMDG, IATA Not classified as hazardous for transport

Environmental hazards:

· Marine pollutant: No

Special precautions for user Warning: Gases.

Hazard identification number (Kemler code):

· EMS Number: F-D.S-U

Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity

of 1 litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of

class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of

class 2.

· Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category

Tunnel restriction code

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

·Safety, health and environmental regulations/legislation specific for the substance or mixture

D

· Australian Inventory of Industrial Chemicals		
106-97-8	butane, pure	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	
74-98-6	propane	
	(Contd. on page 11)	

Revision: 16.04.2022

Printing date 29.01.2024

Version number 3.2

Trade name: ANTIRUST SPRAY

		(Contd. of page 10)
71-36-3	butan-1-ol	
75-28-5	isobutane	
123-86-4	n-butyl acetate	
26566-95-0	Zinkbis[O-(2-ethylhexyl)]bis[O-(isobutyl)]bis(dithiophosphat)	
78-78-4	isopentane	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
98-82-8	Cumene	
9006-04-6	Natural rubber latex	
· Standard fo	or the Uniform Scheduling of Medicines and Poisons	
71-36-3 but	tan-1-ol	S5, S6
· Australia: F	Priority Existing Chemicals	
None of the	ingredients is listed.	

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Contact:
- · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.