Revision: 20.06.2023

Printing date 29.01.2024

Version number 5.0

1 Identification

- · Product identifier
- · Trade name: ATF DEXRON III
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture

Gear Oil

Only for proper handling.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- Signal word Void
- · Hazard statements Void
- · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 72623-87-1 EINECS: 276-738-4	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	25-50%
Index number: 649-483-00-5		
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1, H304	≥10-≤25%



Printing date 29.01.2024 Version number 5.0 Revision: 20.06.2023

Trade name: ATF DEXRON III

		(Contd. of page 1)
CAS: 64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	≥1-≤3%
EINECS: 265-158-7	Asp. Tox. 1, H304	
Index number: 649-468-00-3		
CAS: 64742-65-0	Distillates (petroleum), solvent-dewaxed heavy	≥0.25-≤2.5%
EINECS: 265-169-7	paraffinic	
Index number: 649-474-00-6	Asp. Tox. 1, H304	

Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove contaminated clothing immediately.

Remove residues with soap and water.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Consult a physician who will decide on need and method of emptying the stomach.

Do not induce vomitting. Do not take in resorption stimulating agents.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and nitrogen oxides can be formed.

· Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

AU

Revision: 20.06.2023

Printing date 29.01.2024 Version number 5.0

Trade name: ATF DEXRON III

(Contd. of page 2)

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap. No special measures required.

- · Information about fire and explosion protection: Do not heat above flash point.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

- Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs					
72623-87-	72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3/8h (worker)			
	DNEL/general population/Local effects/Long-term	1.2 mg/m3/24h (consumer)			
64742-55-	64742-55-8 Distillates (petroleum), hydrotreated light paraffinic				
Dermal	DNEL / Workers / Local Effects / Long-term	1 mg/kg/8h (worker)			
Inhalative	DNEL	2.7-5.4 mg/m3/8h (worker)			
	DNEL	1.2 mg/m3/24h (consumer)			
64742-65-	64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic				
Inhalative	DNEL	5.4 mg/m3/8h (worker)			
	DNEL	1.2 mg/m3/24h (consumer)			

· PNECs

64742-55-8 Distillates (petroleum), hydrotreated light paraffinic

Oral PNEC / Predators / Secondary poisoning | 9.33 mg/kg food (secondary poisoning (predators))

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore (Contd. on page 4)



Printing date 29.01.2024 Version number 5.0 Revision: 20.06.2023

Trade name: ATF DEXRON III

(Contd. of page 3)

to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

· Form: Fluid · Colour: Red

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/freezing point:
 Initial boiling point and boiling range:
 Flash point:
 Flammability (solid, gas):
 Undetermined.
 >170 °C
 Not applicable.

Flammability (solid, gas):
 Auto-ignition temperature:
 Decomposition temperature:
 Not applicable.
 >260 °C (DIN 51794)
 Not determined.

· Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.

• Density at 20 °C: 0.857 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

· water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• Dynamic: Not determined.
 • Kinematic: 39 mm²/s @ 40 °C

· Solvent separation test:

· **VOC (EC)** 0.00 %

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

AU

MOTOREX Oil of Switzerland
Revision: 20.06.2023

Printing date 29.01.2024

Version number 5.0

Trade name: ATF DEXRON III

(Contd. of page 4)

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values rele	evant for classification:
72623-87-	1 Lubricat	ing oils (petroleum), C20-50, hydrotreated neutral oil-based
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)
64742-54-	7 Distillate	es (petroleum), hydrotreated heavy paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
64742-55-		es (petroleum), hydrotreated light paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative		2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
		es (petroleum), solvent-dewaxed heavy paraffinic
Oral	LD50	5,000 mg/kg (rat)
D	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
ınhalative	LC50 / 4h	2.18-5.53 mg/l (rat) (Contd. on pa

(Contd. on page 6)

Revision: 20.06.2023

Printing date 29.01.2024

Version number 5.0

Trade name: ATF DEXRON III

	(Contd. of	f page 5)
NOEL	220 mg/m3 (rat)	
NOAEL	980 mg/m3 (rat)	
01-1 1 /!!!	tion December of the late of the december of the line of the december of the late of the l	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information			
	40 E		
		TATAITALI	
		197911 92 911	

Toxicity

•	c toxicity: 87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
64742-	54-7 Distillates (petroleum), hydrotreated heavy paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
64742-	55-8 Distillates (petroleum), hydrotreated light paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
	>100 mg/l/96h (Pimephales promelas) (OECD 203)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
NOEL	>100 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201)
	65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)

(Contd. on page 7)

MOTOREX*
Oil of Switzerland

Revision: 20.06.2023

Printing date 29.01.2024 Version number 5.0

Trade name: ATF DEXRON III

(Contd. of page 6)

Behaviour in environmental systems:

•
· Bioaccumulative potential
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic
Partition coefficient >6 [] (log Kow) (Bioaccumulation)
64742-55-8 Distillates (petroleum), hydrotreated light paraffinic
Partition coefficient >3.5 [] (log Kow) (Bioaccumulation)
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic
Partition coefficient >6 [] (log Kow) (Bioaccumulation)

- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number ADG, ADN, IMDG, IATA	Not classified as hazardous for transport
IN proper shipping name NDG, ADN, IMDG, IATA	Not classified as hazardous for transport
Transport hazard class(es)	
ADG, ADN, IMDG, IATA Class	Not classified as hazardous for transport
acking group DG, IMDG, IATA	Not classified as hazardous for transport
invironmental hazards: farine pollutant:	No
Special precautions for user	Not applicable.
Special precautions for user Transport in bulk according to Anno Marpol and the IBC Code	• • • • • • • • • • • • • • • • • • • •

(Contd. on page 8)

Revision: 20.06.2023

Printing date 29.01.2024

Version number 5.0

Trade name: ATF DEXRON III

(Contd. of page 7)

· UN "Model Regulation": Not classified as hazardous for transport

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian	Inventory of Industrial Chemicals	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	
18760-44-6	3-(decyloxy)tetrahydrothiophene 1,1-dioxide	
72623-86-0	Lubricating oils, C15-30, hydrotreated neutral oil-based	
61791-44-4	Ethanol, 2,2'-iminobis-, N-tallow alkylderivs.	
30113-45-2	3-(isodecyloxy)propylamine	
73984-93-7	1,3,4-Thiadiazole-2(3H)-thione, 5-(tert-dodecyldithio)-	
29385-43-1	methyl-1H-benzotriazole	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· Standard fo	or the Uniform Scheduling of Medicines and Poisons	
1330-20-7	kylene	S6
Australia: F	Priority Existing Chemicals	

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- · Relevant phrases

H304 May be fatal if swallowed and enters airways.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Contact:
- · Abbreviations and acronyms:

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.