MOTOREX
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

#### 1 Identification

- · Product identifier
- · Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture

Only for proper handling.

Chain lubricant

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

**MOTOREX AG** 

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

### 2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if

heated.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Polysulfides, di-tert-dodecvl

Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

MOTOREX\*
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 1)

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### 3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	25-50%
EC number: 927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	5-10%
EC number: 934-956-3	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304	2.5-7.5%
EC number: 920-107-4	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304	2.5-7.5%
EC number: 934-954-2	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics Asp. Tox. 1, H304	2.5-7.5%
EC number: 932-020-9	Hydrocarbons, C8-C9, isoalkanes Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	≥1-<2.5%
CAS: 68425-15-0 EINECS: 270-335-7	Polysulfides, di-tert-dodecyl Skin Sens. 1B, H317	≥1-≤2.5%
	Skin Sens. 1B, H31/ Man detergents / Labelling for contents	

# Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons ≥15 - <30%</li> optical brighteners <5%</li>

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First Aid Measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

MOTOREX\*
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire Fighting Measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

#### 6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- Storage class: 2 B
- · Specific end use(s) No further relevant information available.

ΑU

Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 3)

#### 8 Exposure controls and personal protection

106-97-8	butane, pure	•
	g-term value: 1900 mg/m³, 800 ppm	
74-98-6 pi		
WES Asp	•	
DNELs	<u>·</u>	
Hydrocar	bons, C9-C10, n-alkanes, isoalkanes, cyclic	s, < 2% aromatics
Oral	DNEL/general population/Systemic effects/Lo	ng-term 125 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-ter	m 208 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Lo	ng-term 125 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-ter	m 871 mg/m3 (worker)
	DNEL/general population/Systemic effects/Lo	ng-term 185 mg/m3 (consumer)
Hydrocar	bons, C15-C20 n-alkanes, isoalkanes, cyclo	alkanes, <0.03% aromatics
Dermal	DNEL / Workers / Systemic effects / Long-ter	m 2.9 mg/kg/24h (worker)
Inhalative	DNEL / Workers / Systemic effects / Long-term 16 mg/m3 (worker)	
68425-15-	0 Polysulfides, di-tert-dodecyl	·
Oral	DNEL/general population/Systemic effects/Lo	ng-term 1.66 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-ter	m 33.3 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Lo	ng-term 16.66 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-ter	m 23.5 mg/m3 (worker)
DNEL/general population/Systemic effects/Long-term		ng-term 5.8 mg/m3 (consumer)
PNECs		
68425-15-	0 Polysulfides, di-tert-dodecyl	

PNEC/Aquatic organisms/Sewage treatment 1,000 mg/l (aquatic organisms) plant/STP

- · Additional information: The lists valid during the making were used as basis.
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)



Printing date 29.01.2024 Version number 2.2 Revision: 17.04.2023

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 4)

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

· Body protection: Protective work clothing

### 9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Liquefied gasColour: yellow fluorescent

· Odour: Mild

Odour threshold: Not determined.pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: Not applicable, as aerosol.

Flash point:
 Flammability (solid, gas):
 Auto-ignition temperature:
 Decomposition temperature:
 Not applicable.
 365 °C (DIN 51794)
 Not determined.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol %
 Upper: 8.5 Vol %
 Vapour pressure at 20 °C: 2,100 hPa

• **Density at 20 °C:** 0.711 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

**Dynamic:** Not determined.

★ Kinematic: < 3 mm²/s @ 40 °C (DIN 51562-1)
</p>

· Solvent separation test:

· **VOC (EC)** 50.00 %

· Other information No further relevant information available.

### 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

(Contd. on page 6)

MOTOREX\*
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 5)

- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

		t for classification:
	butane, pure	1440 700 4440 #440
Inhalative	1	1,442.738-1.443 mg/l (rat)
	l	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	LC50 / 4h	658 mg/l (rat)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.2-21.4 mg/l (rat)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)
Hydrocar	bons, C9-C10,	n-alkanes, isoalkanes, cyclics, < 2% aromatics
Oral	LD50	5,000-15,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
		3,160-5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)
	LC50 / 8h	41-4,467 ppm (rat)
	LC50 / 8h	5 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m3 (rat)
Hydrocar	bons, C15-C20	n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1.72-4.6 mg/l (rat)
Hydrocar	bons, C12-C15	, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
Oral	LD50	5,000-15,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
		3,160-5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)
	LC50 / 8h	41-4,467 ppm (rat)
	LC50 / 8h	5 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m3 (rat)
		<u> </u>
Hydrocar	bons, C13-C16	6, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics
<b>Hydrocar</b> Oral	<b>bons, C13-C16</b>   LD50	5, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics  5,000 mg/kg (rat)
-		
-	LD50	5,000 mg/kg (rat)

(Contd. on page 7)

MOTOREX\*
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

		(Contd. of page 6)	
	NOAEC	10.4 mg/l (rat)	
68425-15-	68425-15-0 Polysulfides, di-tert-dodecyl		
Oral	LD50	19,550 mg/kg (rat)	
	NOAEL	1,000 mg/kg/24h (rat)	
Dermal	LD50	2,000 mg/kg (rat)	
Inhalative	LC50 / 4h	15.5 mg/l (rat)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.

10 Eac	Jagiaal	Inform	ation
12 EC0	iogical	Inform	เสแบท

7	οx	cic	it:	V

•	· Toxicity		
· Aquatic	· Aquatic toxicity:		
106-97-8	8 butane, pure		
LC50	24.1-147.5 mg/l/96h (fish)		
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)		
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)		
Hydroca	arbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
LL50	10-30 mg/l/96h (fish)		
LL50	10-30 mg/l/72h (fish)		
LL50	100 mg/l/48h (fish)		
LL50	100 mg/l/24h (fish)		
LL0	10 mg/l/96h (aquatic invertebrates)		
	1 mg/l/96h (fish)		
EL50	22-46 mg/l/48h (aquatic invertebrates)		
	1,000 mg/l/48h (algae / cyanobacteria)		
EL50	100 mg/l/24h (aquatic invertebrates)		
	1,000 mg/l/24h (algae / cyanobacteria)		
EL50	1,000 mg/l/72h (algae / cyanobacteria)		
EL0	10 mg/l/48h (aquatic invertebrates)		
NOELR	0.182 mg/l/28d (fish)		
NOELR	0.317 mg/l/21d (aquatic invertebrates)		
NOELR	1,000 mg/l/72h (algae / cyanobacteria)		
Hydroca	arbons, C12-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
LL50	1,000 mg/l/96h (fish)		
LL50	1,000 mg/l/72h (fish)		
LL50	1,000 mg/l/48h (fish)		
LL50	1,000 mg/l/24h (fish)		
LL0	1,000 mg/l/96h (fish)		
EL50	1,000 mg/l/48h (aquatic invertebrates)		
EL50	1,000 mg/l/24h (aquatic invertebrates)		
	(Contd. on page 8)		

(Contd. on page 8)

MOTOREX Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

	(Contd. of page 7)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
NOELR	1,000 mg/l/28d (fish)
NOELR	1,000 mg/l/21d (aquatic invertebrates)
NOELR	1,000 mg/l/72h (algae / cyanobacteria)
Hydroca	nrbons, C13-C16, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics
EC50	100 mg/l/3h (microorganisms)
LL50	1.028 mg/l/96h (fish)
LL50	3.193 mg/l/48h (aquatic invertebrates)
LL50	3.193 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/72h (algae / cyanobacteria)
NOELR	1,000 mg/l/28d (fish)
NOELR	1,000 mg/l/21d (aquatic invertebrates)
68425-1	5-0 Polysulfides, di-tert-dodecyl
LC50	100 mg/l/96h (fish)
LC0	100 mg/l/96h (fish)
LL50	100 mg/l/96h (fish)
NOEC	0.08 mg/l/72h (algae / cyanobacteria)
	10-10,000 mg/l/72h (microorganisms)
NOEC	100 mg/l/96h (fish)
NOEC	0.1 mg/l/48h (aquatic invertebrates)

- Persistence and degradability Biodegradability (CEC L-33-A-93):> 75%
- Behaviour in environmental systems:

Denaviour in environmental systems.			
· Bioaccumulative p	· Bioaccumulative potential		
106-97-8 butane, p	ure		
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)		
Hydrocarbons, C9	-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Biodegradability	>80 % (28d) (Biodegradability) (OECD 301 F)		
Hydrocarbons, C1	2-C15, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Biodegradability	2 % (28d) (Biodegradability) (OECD 301 F)		
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cycloalkanes, <12:03% aromatics			
Biodegradability	74 % (28d) (Biodegradability) (OECD 306)		
68425-15-0 Polysu	68425-15-0 Polysulfides, di-tert-dodecyl		
Partition coefficient	6.2-12.45 [] (log Kow) (Bioaccumulation)		

- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

ΑU

Revision: 17.04.2023 Printing date 29.01.2024 Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 8)

### 13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- · Recommendation:

· Segregation Code

Disposal must be made according to official regulations.

Transport information  UN-Number ADG, IMDG, IATA UN proper shipping name ADG IMDG AEROSOLS IATA AEROSOLS, flamma  Transport hazard class(es)  ADG  Class Label Class Label 2.1  IMDG, IATA  Class Label 2.1  Packing group ADG, IMDG, IATA  Packing group ADG, IMDG, IATA  Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): EMS Number: F-D,S-U  No  VN1950  UN1950  UN1950  AEROSOLS A	
ADG, IMDG, IATA  UN1950  UN proper shipping name ADG IMDG AEROSOLS IATA AEROSOLS, flamma  Transport hazard class(es)  ADG  Class Label  Class AEROSOLS, flamma  AEROSOLS  AIGUS  AEROSOLS  AIGUS  AEROSOLS  AIGUS  AEROSOLS	
UN proper shipping name ADG IMDG AEROSOLS IATA AEROSOLS, flamma  Transport hazard class(es)  ADG  Class Label Class Clas	
ADG IMDG IATA  Interpret hazard class(es)  ADG  Class Label  Class Lab	
IMDG IATA  AEROSOLS AEROSOLS, flamma  Transport hazard class(es)  ADG  Class Label	
IATA AEROSOLS, flamma Transport hazard class(es)  ADG  Class 2 5F Gases. Label 2.1  IMDG, IATA  Class 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haz.  Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): -	
Class 25F Gases. Label 2.1  IMDG, IATA  Class 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze  Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): -	ble
Class 2 5F Gases. Label 2.1  IMDG, IATA  Class 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze. Environmental hazards: Marine pollutant: No  Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -	
Class 2 5F Gases. Label 2.1  IMDG, IATA  Class 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze  Environmental hazards: Marine pollutant: No  Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -	
Label 2.1  IMDG, IATA  Class Label 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): -	
Label 2.1  IMDG, IATA  Class Label 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): -	
Label 2.1  IMDG, IATA  Class Label 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): -	
Label 2.1  IMDG, IATA  Class Label 2.1 Gases. Label 2.1  Packing group ADG, IMDG, IATA Not classified as haze Environmental hazards: Marine pollutant: No  Special precautions for user Hazard identification number (Kemler code): -	
IMDG, IATA  Class Label  Packing group ADG, IMDG, IATA  Environmental hazards: Marine pollutant:  No  Special precautions for user Hazard identification number (Kemler code): -	
Class Label  Packing group ADG, IMDG, IATA  Environmental hazards: Marine pollutant:  Special precautions for user Hazard identification number (Kemler code): -	
Label2.1Packing groupNot classified as hazeADG, IMDG, IATANot classified as hazeEnvironmental hazards:NoMarine pollutant:NoSpecial precautions for userWarning: Gases.Hazard identification number (Kemler code): -	
Label2.1Packing groupNot classified as hazeADG, IMDG, IATANot classified as hazeEnvironmental hazards:NoMarine pollutant:NoSpecial precautions for userWarning: Gases.Hazard identification number (Kemler code): -	
Label2.1Packing groupNot classified as hazeADG, IMDG, IATANot classified as hazeEnvironmental hazards: Marine pollutant:NoSpecial precautions for user Hazard identification number (Kemler code): -Warning: Gases.	
Label2.1Packing groupNot classified as hazeADG, IMDG, IATANot classified as hazeEnvironmental hazards: Marine pollutant:NoSpecial precautions for user Hazard identification number (Kemler code): -Warning: Gases.	
Packing group ADG, IMDG, IATA Not classified as haze Environmental hazards: Marine pollutant: No Special precautions for user Hazard identification number (Kemler code): -	
ADG, IMDG, IATA  Not classified as haze Environmental hazards:  Marine pollutant:  Special precautions for user Hazard identification number (Kemler code): -	
Environmental hazards: Marine pollutant: No Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -	
Marine pollutant: No Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -	ardous for transport
Special precautions for user Warning: Gases. Hazard identification number (Kemler code): -	
Hazard identification number (Kemler code): -	
F.D S.II	
,	
Stowage Code SW1 Protected from	sources of heat. ILS with a maximum ca

of 1 litre:

(Contd. on page 10)

AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity

Segregation as for class 9. Stow "separated from"

MOTOREX\*
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

	(Contd. of page 9
•	class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision o class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision o class 2.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· Transport category · Tunnel restriction code	2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

mixture			
· Australian Inv	ventory of Industrial Chemicals		
106-97-8	butane, pure		
74-98-6	propane		
75-28-5	isobutane		
68425-15-0	Polysulfides, di-tert-dodecyl		
78-78-4	isopentane		
1471316-72-9	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts		
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic		
7128-64-5	2,5-thiophenediylbis(5-tert-butyl-1,3-benzoxazole)		
64741-96-4	Distillates (petroleum), solvent-refined heavy naphthenic		
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic		
72623-86-0	Lubricating oils, C15-30, hydrotreated neutral oil-based		
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based		
· Standard for the Uniform Scheduling of Medicines and Poisons			
None of the ing	None of the ingredients is listed.		
· Australia: Prid	· Australia: Priority Existing Chemicals		
None of the ingredients is listed.			

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 11)

MOTOREX\*
Oil of Switzerland
Revision: 17.04.2023

Printing date 29.01.2024

Version number 2.2

Trade name: CHAINLUBE FOR WET CONDITIONS SPRAY

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

#### purity requirement

#### Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

#### · Department issuing SDS: Abteilung Produktsicherheit

Contact:

#### · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3 Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.

AU