



1 Identification

- **Product identifier**
- **Trade name:** CHAINLUBE ROAD STRONG
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Chain lubricant
Only for proper handling.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTOREX AG
Bern–Zürich–Strasse 31, Postfach
CH–4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com

A1 Accessory Imports
60-62 Burchill St.
Loganholme
4129 QLD
Australia
Phone : 07 3451 1300
- **Further information obtainable from:** msds@motorex.com
- **Emergency telephone number:**
In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

- **Classification of the substance or mixture**
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**
 
GHS02 GHS07
- **Signal word** Danger
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P280 Wear protective gloves.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	10-25%
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; STOT SE 3, H336	≥10-<20%
	Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<20%
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	≥10-<20%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	0.25-1%

- **Regulation (EC) No 648/2004 on detergents / Labelling for contents**

aliphatic hydrocarbons	≥30%
------------------------	------

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.

AU

(Contd. on page 3)

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 2)

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
The recommended storage temperature is (deg.C): ≤50°C
Keep container tightly sealed.
- **Storage class:** 2 B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane, pure

WES | Long-term value: 1900 mg/m³, 800 ppm

74-98-6 propane

WES | Asphyxiant

110-54-3 n-hexane

WES | Long-term value: 72 mg/m³, 20 ppm

· **DNELs**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m ³ (worker)
	DNEL/general population/Systemic effects/Long-term	608 mg/m ³ (consumer)

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 3)

Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan		
Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)
Inhalative	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)
	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m3 (worker)
	DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Oral	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	300 mg/kg/24h (worker)
Inhalative	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)
	DNEL / Workers / Systemic effects / Long-term	1,500 mg/m3 (worker)
	DNEL/general population/Systemic effects/Long-term	900 mg/m3 (consumer)

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Do not inhale gases / fumes / aerosols.
 - Avoid contact with the skin.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - Not necessary if room is well-ventilated.
 - Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.
- **Body protection:** Protective work clothing

9 Physical and Chemical Properties

- **General Information**
- **Appearance:**
- **Form:** Liquefied gas
- **Colour:** white
- **Odour:** Solvent-like
- **Odour threshold:** Not determined.

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 4)

· pH-value:	Not determined.
· Change in condition	
· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	Not applicable, as aerosol.
· Flash point:	<-20 °C
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.78 g/cm ³ (ASTM D 4052)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
· water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	20 mm ² /s @ 40 °C
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

106-97-8 butane, pure

Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	LC50 / 4h	658 mg/l (rat)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.2-21.4 mg/l (rat)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 5)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
Inhalative	LD50	2,800-3,100 mg/kg (rat)
	LC50 / 4h	23.3 mg/l (rat)
	NOAEC	5.8-24.3 mg/l (rat)
Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan		
Oral	LD50	8 ml/kg (rat)
Dermal	LD50	4 ml/kg (rat)
Inhalative	LD50	2,800-3,100 mg/kg (rat)
	LC50 / 4h	25.2 mg/l (rat)
	NOAEC	8.117-24.3 mg/l (rat)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Oral	LD50	5,000-15,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
		3,160-5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)
	LC50 / 8h	41-4,467 ppm (rat)
	LC50 / 8h	5 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m ³ (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aquatic toxicity:

106-97-8 butane, pure

LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	3-10 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
LL50	30-100 mg/l/24h (fish)
LL0	3 mg/l/96h (fish)

(Contd. on page 7)

AU

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 6)

EL50	13 mg/l/96h (algae / cyanobacteria)
EL50	4.6-10 mg/l/48h (aquatic invertebrates)
	10-30 mg/l/48h (algae / cyanobacteria)
EL50	10-22 mg/l/24h (aquatic invertebrates)
	10-30 mg/l/24h (algae / cyanobacteria)
EL50	10-30 mg/l/72h (algae / cyanobacteria)
EL0	4.6 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	0.574 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
NOELR	6.3 mg/l/96h (algae / cyanobacteria)
LOEC	0.32 mg/kg/28d (aquatic invertebrates)

Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan

EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	11.4 mg/l/96h (fish)
LL50	15.8 mg/l/72h (fish)
LL0	5.1 mg/l/96h (fish)
EL50	3 mg/l/48h (aquatic invertebrates)
EL50	12 mg/l/24h (aquatic invertebrates)
EL50	10-100 mg/l/72h (algae / cyanobacteria)
EL0	2 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	2.045 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
LOEC	0.32 mg/kg/28d (aquatic invertebrates)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics

LL50	1,000 mg/l/96h (fish)
LL50	1,000 mg/l/72h (fish)
LL50	1,000 mg/l/48h (fish)
LL50	1,000 mg/l/24h (fish)
LL0	100 mg/l/96h (fish)
EL50	1,000 mg/l/48h (aquatic invertebrates)
EL50	1,000 mg/l/24h (aquatic invertebrates)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
NOELR	0.131 mg/l/28d (fish)
NOELR	0.23 mg/l/21d (aquatic invertebrates)
NOELR	3-100 mg/l/72h (algae / cyanobacteria)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential**

106-97-8 butane, pure

Partition coefficient | 1.09-2.8 [---] (log Kow) (Bioaccumulation)

(Contd. on page 8)

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 7)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Biodegradability	98 % (28d) (Biodegradability) (OECD 301 F)
Kohlenwasserstoffe C6-C7, n-Alkane, Isoalkane, Cyclene, <5% n-Hexan	
Biodegradability	81 % (28d) (Biodegradability) (OECD 301 F)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	
Biodegradability	80 % (28d) (Bioaccumulation) (OECD 301 F)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Contact waste processors for recycling information.
Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Discharged containers can contain flammable or explosive vapours.

14 Transport information

· UN-Number	UN1950
· ADG, IMDG, IATA	
· UN proper shipping name	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· ADG	
· IMDG	AEROSOLS, MARINE POLLUTANT
· IATA	AEROSOLS, flammable
· Transport hazard class(es)	
· ADG	
· Class	2 5F Gases.

(Contd. on page 9)

AU

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 8)

· **Label** 2.1· **IMDG**

· **Class** 2.1 Gases.
 · **Label** 2.1

· **IATA**

· **Class** 2.1 Gases.
 · **Label** 2.1

· **Packing group**· **ADG, IMDG, IATA** Not classified as hazardous for transport· **Environmental hazards:**· **Marine pollutant:** Symbol (fish and tree)· **Special marking (ADG):** Symbol (fish and tree)· **Special precautions for user** Warning: Gases.· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code**· **Segregation Code**

SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
 SG69 For AEROSOLS with a maximum capacity of 1 litre:
 Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
 For AEROSOLS with a capacity above 1 litre:
 Segregation as for the appropriate subdivision of class 2.
 For WASTE AEROSOLS:
 Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **ADG**· **Limited quantities (LQ)** 1L· **Excepted quantities (EQ)** Code: E0

Not permitted as Excepted Quantity

· **Transport category** 2· **Tunnel restriction code** D· **IMDG**· **Limited quantities (LQ)** 1L

(Contd. on page 10)

AU

Safety Data Sheet

according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 9)

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

106-97-8	butane, pure
9003-29-6	Polybuten (Isobutylen-/Buten-Copolymer)
74-98-6	propane
75-28-5	isobutane
110-54-3	n-hexane
78-78-4	isopentane
110-82-7	cyclohexane
95-38-5	2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol
110-25-8	(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine

· **Standard for the Uniform Scheduling of Medicines and Poisons**

None of the ingredients is listed.

· **Australia: Priority Existing Chemicals**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· **purity requirement**

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

(Contd. on page 11)

Safety Data Sheet
according to WHS Regulations



Printing date 26.03.2024

Version number 1.0

Revision: 26.03.2024

Trade name: CHAINLUBE ROAD STRONG

(Contd. of page 10)

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Abteilung Produktsicherheit

· **Contact:**

· **Abbreviations and acronyms:**

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

AU