

1 Identification

- **Product identifier**
- **Trade name:** COLOUR SPRAY BLACK
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Colour spray
Only for proper handling.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTOREX AG
Bern-Zürich-Strasse 31, Postfach
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com

A1 Accessory Imports
60-62 Burchill St.
Loganholme
4129 QLD
Australia
Phone : 07 3451 1300
- **Further information obtainable from:** msds@motorex.com
- **Emergency telephone number:**
In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

- **Classification of the substance or mixture**

Aerosol 1	H222-H229	Extremely flammable aerosol.
		Pressurised container: May burst if heated.
Serious eye damage/irritation – Category 2A	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**
The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**
acetone
ethyl acetate
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 1)

- P102 Keep out of reach of children.
 P103 Read label before use.
 P211 Do not spray on an open flame or other ignition source.
 P251 Pressurized container: Do not pierce or burn, even after use.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥20-≤25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥20-≤25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	≥5-≤10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	≥5-≤10%
CAS: 1330-20-7 Index number: 601-022-00-9	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H335	≥1-≤2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 2)

5 Fire Fighting Measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
Do not spray onto a naked flame or any incandescent material.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WES	Short-term value: 2375 mg/m ³ , 1000 ppm Long-term value: 1185 mg/m ³ , 500 ppm
-----	--

141-78-6 ethyl acetate

WES	Short-term value: 1440 mg/m ³ , 400 ppm Long-term value: 720 mg/m ³ , 200 ppm
-----	--

108-65-6 2-methoxy-1-methylethyl acetate

WES	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 3)

123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

1330-20-7 xylene

WES Short-term value: 655 mg/m³, 150 ppm
Long-term value: 350 mg/m³, 80 ppm

· DNELs**141-78-6 ethyl acetate**

Oral	DNEL/general population/Systemic effects/Long-term	4.5 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	63 mg/kg/24h (worker)
Inhalative	DNEL/general population/Systemic effects/Long-term	37 mg/kg/24h (consumer)
	DNEL / Workers / Systemic effects / Long-term	734 mg/m ³ (worker)
	DNEL/Workers/Systemic effects/acute-short term	1,468 mg/m ³ (worker)
	DNEL/Workers/Local effects/acute-short term	1,468 mg/m ³ (worker)
	DNEL / Workers / Local Effects / Long-term	734 mg/m ³ (worker)
	DNEL/general population/Systemic effects/Long-term	367 mg/m ³ (consumer)
	DNEL/general pop/Systemic effects/acute-short term	734 mg/m ³ (consumer)
	DNEL/general pop/Local effects/acute-short term	734 mg/m ³ (consumer)
	DNEL/general population/Local effects/Long-term	367 mg/m ³ (consumer)

123-86-4 n-butyl acetate

Oral	DNEL/general population/Systemic effects/Long-term	2 mg/kg/24h (consumer)
	DNEL/general pop/Systemic effects/acute-short term	2 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	7 mg/kg/24h (worker)
	DNEL/Workers/Systemic effects/acute-short term	11 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	3.4 mg/kg/24h (consumer)
Inhalative	DNEL/general pop/Systemic effects/acute-short term	6 mg/kg/24h (consumer)
	DNEL / Workers / Systemic effects / Long-term	48 mg/m ³ (worker)
	DNEL/Workers/Systemic effects/acute-short term	600 mg/m ³ (worker)
	DNEL/Workers/Local effects/acute-short term	600 mg/m ³ (worker)
	DNEL / Workers / Local Effects / Long-term	300 mg/m ³ (worker)
	DNEL/general population/Systemic effects/Long-term	12 mg/m ³ (consumer)
	DNEL/general pop/Systemic effects/acute-short term	300 mg/m ³ (consumer)
	DNEL/general pop/Local effects/acute-short term	300 mg/m ³ (consumer)
	DNEL/general population/Local effects/Long-term	35.7 mg/m ³ (consumer)

1330-20-7 xylene

Oral	DNEL/general population/Systemic effects/Long-term	1.6 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long-term	180 mg/kg/24h (worker)
	DNEL/general population/Systemic effects/Long-term	108 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long-term	77 mg/m ³ (worker)
	DNEL/Workers/Local effects/acute-short term	289 mg/m ³ (worker)
	DNEL/general population/Systemic effects/Long-term	14.8 mg/m ³ (consumer)

· PNECs**67-64-1 acetone**

PNEC / Aquatic organisms / Freshwater	10.6 mg/l (aquatic organisms)
PNEC / Aquatic organisms / Marine water	1.06 mg/l (aquatic organisms)

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 4)

	<i>PNEC / Aquatic org / intermittent releases (freshwater)</i>	<i>21 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sewage treatment plant / STP</i>	<i>100 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (freshwater)</i>	<i>30.4 mg/kg (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (marine water)</i>	<i>3.04 mg/kg (aquatic organisms)</i>
	<i>PNEC / Terrestrial organism / Soil</i>	<i>29.5 mg/kg (aquatic organisms)</i>
141-78-6 ethyl acetate		
Oral	<i>PNEC / Predators / Secondary poisoning</i>	<i>200 mg/kg food (secondary poisoning (predators))</i>
	<i>PNEC / Aquatic organisms / Freshwater</i>	<i>0.24 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Marine water</i>	<i>0.024 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic org / intermittent releases (freshwater)</i>	<i>1.65 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sewage treatment plant / STP</i>	<i>650 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (freshwater)</i>	<i>1.15 mg/kg (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (marine water)</i>	<i>0.115 mg/kg (aquatic organisms)</i>
	<i>PNEC / Terrestrial organism / Soil</i>	<i>0.148 mg/kg (terrestrial organisms)</i>
123-86-4 n-butyl acetate		
	<i>PNEC / Aquatic organisms / Freshwater</i>	<i>0.18 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Marine water</i>	<i>0.018 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic org / intermittent releases (freshwater)</i>	<i>0.36 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sewage treatment plant / STP</i>	<i>35.6 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (freshwater)</i>	<i>0.981 mg/kg (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (marine water)</i>	<i>0.0981 mg/kg (aquatic organisms)</i>
	<i>PNEC / Terrestrial organism / Soil</i>	<i>0.0903 mg/kg (terrestrial organisms)</i>
1330-20-7 xylene		
	<i>PNEC / Aquatic organisms / Freshwater</i>	<i>0.327 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Marine water</i>	<i>0.327 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sewage treatment plant / STP</i>	<i>6.58 mg/l (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (freshwater)</i>	<i>12.46 mg/kg (aquatic organisms)</i>
	<i>PNEC / Aquatic organisms / Sediment (marine water)</i>	<i>12.46 mg/kg (aquatic organisms)</i>
	<i>PNEC / Terrestrial organism / Soil</i>	<i>2.31 mg/kg (terrestrial organisms)</i>

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 6)

Trade name: COLOUR SPRAY BLACK

(Contd. of page 5)

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Safety glasses

· **Body protection:** Protective work clothing

9 Physical and Chemical Properties

· **General Information**

· **Appearance:**

· **Form:** Liquefied gas

· **Colour:** Black

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** -42 °C (DIN EN ISO 3405)

· **Flash point:** -100 °C

· **Flammability (solid, gas):** Not applicable.

· **Auto-ignition temperature:** 333 °C (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· **Lower:** 1.9 Vol %

· **Upper:** 13 Vol %

· **Vapour pressure:** 8300 mbar @ 20 °C

· **Density at 20 °C:** 0.84 g/cm³ (ASTM D 4052)

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not applicable.

· **Solubility in / Miscibility with**

· **water:** Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· **Dynamic:** Not determined.

(Contd. on page 7)

Trade name: COLOUR SPRAY BLACK

(Contd. of page 6)

- | | |
|----------------------------|--|
| · Kinematic: | Not determined. |
| · Other information | No further relevant information available. |

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
	NOAEL	20,000 ppm (mouse) 10,000-50,000 ppm (rat)
	LOAEL	50,000 ppm (mouse) 20,000 ppm (rat)
Dermal	LD50	9.4-20 ml/kg (rabbit)
	LD50	7,426-15,800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 8h	50.1 mg/l (rat)
	NOAEC	19,000 ppm (rat)

141-78-6 ethyl acetate

Oral	LD50	4,934 mg/kg (rabbit)
	LD50	11.3 ml/kg (rat)
	NOAEL	900 mg/kg/24h (rat)
	LOAEL	3,600 mg/kg/24h (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	1,600 mg/l (rat)
	NOEC	350 ppm (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50 / 4h	35.7 mg/l (rat)

123-86-4 n-butyl acetate

Oral	LD50	10,736-12,760 mg/kg (rat)
	LD50	12.2-14.5 ml/kg (rat)
Dermal	LD50	16 ml/kg (rabbit)
	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	>21 mg/l (rat)
	LC50 / 4h	1,087-1,109 ppm (rat)

(Contd. on page 8)

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 7)

	LC50 / 4h	740-71,500 mg/m ³ (rat)
	NOAEC	500 ppm (rat)
1330-20-7 xylene		
Oral	LD50	5,251-5,627 mg/kg (mouse) 3,523-4,000 mg/kg (rat)
	NOAEL	150-250 mg/kg/24h (rat)
	LOAEL	150 mg/kg/24h (rat)
Dermal	LD50	5,000 ml/kg (rabbit)
	LD50	12,126 mg/kg (rabbit)
Inhalative	LC50 / 4h	6,350-6,700 ppm (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aquatic toxicity:

67-64-1 acetone

LC50	5,540-8,120 mg/l/96h (fish)
LC50	8,800 mg/l/48h (aquatic invertebrates)
LC50	2,100 mg/l/24h (aquatic invertebrates)
NOEC	1,106-2,212 mg/l/28d (aquatic invertebrates)

141-78-6 ethyl acetate

LC50	230 mg/l/96h (fish)
EC10	2,300 mg/l/48h (algae / cyanobacteria)
EC50	2.306 mg/l/24h (aquatic invertebrates)
EC50	220 mg/l/96h (fish)
EC50	5,600 mg/l/48h (algae / cyanobacteria)
NOEC	2.4 mg/l/21d (aquatic invertebrates)
NOEC	100 mg/l/72h (algae / cyanobacteria)

123-86-4 n-butyl acetate

LC50	18 mg/l/96h (fish)
LC50	43.5 mg/l/21d (aquatic invertebrates)
EC50	18 mg/l/96h (fish)
EC50	246-674.7 mg/l/72h (algae / cyanobacteria)
EC50	34.2 mg/l/21d (aquatic invertebrates)
EC50	32-44 mg/l/48h (aquatic invertebrates)
	392 mg/l/48h (algae / cyanobacteria)
NOEC	23.2 mg/l/21d (aquatic invertebrates)
NOEC	105-196 mg/l/72h (algae / cyanobacteria)
NOEC	196 mg/l/48h (algae / cyanobacteria)

(Contd. on page 9)

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 8)

LOEC	47.6 mg/kg/28d (aquatic invertebrates)
1330-20-7 xylene	
LC50	2.6 mg/l/96h (fish)
EC50	157 mg/l/3h (microorganisms)
EC50	96 mg/l/24h (microorganisms)
EC10	0.72-1.9 mg/l/72h (algae / cyanobacteria)
EC50	2.2-4.36 mg/l/72h (algae / cyanobacteria)
NOEC	0.44 mg/l/72h (algae / cyanobacteria)
NOEC	0.96-1.17 mg/l/7d (aquatic invertebrates)
NOEC	157 mg/l/3h (microorganisms)

· **Persistence and degradability** No further relevant information available.

· **Behaviour in environmental systems:**

· **Bioaccumulative potential**

67-64-1 acetone	
Partition coefficient	-0.23 [---] (log Kow) (Bioaccumulation)
Biodegradability	91 % (28d) (Biodegradability) (OECD 301 B)
141-78-6 ethyl acetate	
Partition coefficient	0.68-0.73 [---] (log Kow) (Bioaccumulation)
Biodegradability	>70 % (28d) (Biodegradability) (BOD)
123-86-4 n-butyl acetate	
Partition coefficient	1.81-2.3 [---] (log Kow) (Bioaccumulation)
Bioconcentration factor (BCF)	15 BCF (Bioaccumulation)
Biodegradability	83 % (28d) (Biodegradability) (OECD 301 D)
1330-20-7 xylene	
Partition coefficient	3.12-3.2 [---] (log Kow) (Bioaccumulation)
Biodegradability	87.8 % (28d) (Biodegradability) (OECD 301 F)

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

(Contd. on page 10)

AU

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1



Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 9)

Discharged containers can contain flammable or explosive vapours.

14 Transport information

· UN-Number · ADG, IMDG, IATA	UN1950
· UN proper shipping name · ADG · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· Transport hazard class(es) · ADG	
	
· Class · Label	2 5F Gases. 2.1
· IMDG, IATA	
	
· Class · Label	2.1 Gases. 2.1
· Packing group · ADG, IMDG, IATA	Not classified as hazardous for transport
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemler code): - · EMS Number: · Stowage Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Segregation Code	
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.

(Contd. on page 11)

AU

Safety Data Sheet

according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 10)

· Transport/Additional information:

· ADG

- Limited quantities (LQ)
- Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

- Transport category
- Tunnel restriction code

2
D

· IMDG

- Limited quantities (LQ)
- Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

67-64-1	acetone	S5
1330-20-7	xylene	S6

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3b FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· purity requirement

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

- Department issuing SDS: Abteilung Produktsicherheit

(Contd. on page 12)

Safety Data Sheet
according to WHS Regulations



Printing date 29.01.2024

Version number 1.1

Revision: 29.01.2024

Trade name: COLOUR SPRAY BLACK

(Contd. of page 11)

· Contact:**· Abbreviations and acronyms:***Aerosol 1: Aerosols – Category 1**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Serious eye damage/irritation – Category 2A: Serious eye damage/eye irritation – Category 2A**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Asp. Tox. 1: Aspiration hazard – Category 1***· * Data compared to the previous version altered.**

—AU—