MOTOREX Oil of Switzerland
Revision: 28.03.2023

Printing date 30.01.2024

Version number 2.1

#### 1 Identification

- · Product identifier
- · Trade name: COPPER SPRAY
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Lubrication, anticorrosive Only for proper handling.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

**MOTOREX AG** 

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

## 2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms





GHS02 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

isopentane

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P211 Do not spray on an open flame or other ignition source.

(Contd. on page 2)

MOTOREX
Oil of Switzerland
Revision: 28.03.2023

Printing date 30.01.2024 Version number 2.1 Re

Trade name: COPPER SPRAY

(Contd. of page 1)

P251 Pressurized container: Do not pierce or burn, even after use. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

### 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EINECS: 203-448-7	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	50-70%
Index number: 601-004-00-0 EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; STOT SE 3, H336	≥10-<20%
Regulation (EC) No 648/2004 on detergents / Labelling for contents		
aliphatic hydrocarbons		≥15 - <30%

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First Aid Measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire Fighting Measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

MOTOREX\*
Oil of Switzerland

Revision: 28.03.2023

Printing date 30.01.2024 Version number 2.1

Trade name: COPPER SPRAY

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and Storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤ 50°C

Keep container tightly sealed.

- · Storage class: 2 B
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredien	· Ingredients with limit values that require monitoring at the workplace:		
106-97-8 I	106-97-8 butane, pure		
WES Lon	WES Long-term value: 1900 mg/m³, 800 ppm		
74-98-6 pi	74-98-6 propane		
WES Asp	WES Asphyxiant		
DNELs	DNELs		
Hydrocar	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)	
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)	
	DNEL/general population/Systemic effects/Long-term 699 mg/kg/24h (consumer)		
Inhalative	Inhalative   DNEL / Workers / Systemic effects / Long-term   2,035 mg/m3 (worker)		
	DNEL/general population/Systemic effects/Long-term 608 mg/m3 (consumer)		

- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

(Contd. on page 4)

MOTOREX Oil of Switzerland

Printing date 30.01.2024 Version number 2.1 Revision: 28.03.2023

Trade name: COPPER SPRAY

(Contd. of page 3)

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Not required.
- · Body protection: Protective work clothing

### 9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Liquefied gas
Colour: Gold coloured
Odour: Solvent-like
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: <0 °C

Flammability (solid, gas):

Auto-ignition temperature:

Decomposition temperature:

Not applicable.

310 °C (DIN 51794)

Not determined.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.9 Vol %
 Upper: 8.5 Vol %
 Vapour pressure at 20 °C: 2,100 hPa

• Density at 20 °C: 0.628 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent separation test:

· **VOC (EC)** 84.00 %

· Other information No further relevant information available.

AU

MOTOREX Oil of Switzerland
Revision: 28.03.2023

Printing date 30.01.2024 Version number 2.1

Trade name: COPPER SPRAY

(Contd. of page 4)

### 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
106-97-8	106-97-8 butane, pure		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)	
	LC50 / 15 min	800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	LC50 / 4h	658 mg/l (rat)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.2-21.4 mg/l (rat)	
	LOAEC	21.6 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	
Hydrocar	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	LD50	8 ml/kg (rat)	
Dermal	LD50	4 ml/kg (rat)	
	LD50	2,800-3,100 mg/kg (rat)	
Inhalative	LC50 / 4h	23.3 mg/l (rat)	
	NOAEC	5.8-24.3 mg/l (rat)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.

#### 12 Ecological Information

· Toxicity

Aquatio	· Aquatic toxicity:	
106-97-	106-97-8 butane, pure	
LC50	24.1-147.5 mg/l/96h (fish)	
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)	
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)	

(Contd. on page 6)

Revision: 28.03.2023

Printing date 30.01.2024

Version number 2.1

Trade name: COPPER SPRAY

	(Contd. of page 5)
	arbons, C7-C9, n-alkanes, isoalkanes, cyclics
EC50	0.23 mg/l/21d (aquatic invertebrates)
EC50	0.64 mg/l/48h (aquatic invertebrates)
LL50	3-10 mg/l/96h (fish)
LL50	10-30 mg/l/72h (fish)
LL50	10-30 mg/l/48h (fish)
LL50	30-100 mg/l/24h (fish)
LL0	3 mg/l/96h (fish)
EL50	13 mg/l/96h (algae / cyanobacteria)
EL50	4.6-10 mg/l/48h (aquatic invertebrates)
	10-30 mg/l/48h (algae / cyanobacteria)
EL50	10-22 mg/l/24h (aquatic invertebrates)
	10-30 mg/l/24h (algae / cyanobacteria)
EL50	10-30 mg/l/72h (algae / cyanobacteria)
EL0	4.6 mg/l/48h (aquatic invertebrates)
EL0	10 mg/l/24h (aquatic invertebrates)
NOEC	0.17 mg/l/21d (aquatic invertebrates)
NOELR	0.574 mg/l/28d (fish)
NOELR	1 mg/l/21d (aquatic invertebrates)
NOELR	6.3 mg/l/96h (algae / cyanobacteria)
LOEC	0.32 mg/kg/28d (aquatic invertebrates)

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:

· Bioaccumulative potential	
106-97-8 butane, pure	
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Biodegradability	98 % (28d) (Biodegradability) (OECD 301 F)

- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

(Contd. on page 7)

MOTOREX Oil of Switzerland
Revision: 28.03.2023

Printing date 30.01.2024 Version number 2.1

Trade name: COPPER SPRAY

(Contd. of page 6)

- · Uncleaned packaging:
- Recommendation:

· Stowage Code

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

Transport information	
UN-Number ADG, IMDG, IATA	UN1950
UN proper shipping name ADG	1950 AEROSOLS, ENVIRONMENT HAZARDOUS
IMDG IATA	AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable
Transport hazard class(es)	
ADG	
<b>Y</b> 2	
Class Label	2 5F Gases. 2.1
IMDG	
¥2	
Class Label	2.1 Gases. 2.1
IATA	
Class Label	2.1 Gases. 2.1
Packing group ADG, IMDG, IATA	Not classified as hazardous for transport
Environmental hazards:	Product contains environmentally haza substances: Hydrocarbons, C7-C9, n-alk isoalkanes, cyclics
Marine pollutant:	No
Special marking (ADG):	Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user	Warning: Gases.

(Contd. on page 8)

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE

MOTOREX\*
Oil of Switzerland
Revision: 28.03.2023

Printing date 30.01.2024 Version number 2.1

Trade name: COPPER SPRAY

	(Contd. of page
Segregation Code	AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL HAZARDOUS

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

mixture			
· Australian l	· Australian Inventory of Industrial Chemicals		
106-97-8	butane, pure		
74-98-6	propane		
<i>75-28-5</i>	isobutane		
78-78-4	isopentane		
7440-50-8	copper		
7440-66-6	zinc powder -zinc dust (stabilized)		
38900-29-7	Dilithium azelate		
· Standard fo	· Standard for the Uniform Scheduling of Medicines and Poisons		
None of the ingredients is listed.			
Δustralia: F	· Australia: Priority Existing Chemicals		

· Australia. Priority Existing Chemicals

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 9)

Version number 2.1

MOTOREX Oil of Switzerland
Revision: 28.03.2023

Printing date 30.01.2024

Trade name: COPPER SPRAY

(Contd. of page 8)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Contact:
- · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.

ALI