

Safety Data Sheet

according to WHS Regulations



Printing date 30.01.2024

Version number 3.1

Revision: 30.10.2023

1 Identification

- **Product identifier**
- **Trade name:** CROSS POWER 4T SAE 10W/50 JASO MA2
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Only for proper handling.
Engine oil
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
MOTOREX AG
Bern-Zürich-Strasse 31, Postfach
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
www.motorex.com

A1 Accessory Imports
60-62 Burchill St.
Loganholme
4129 QLD
Australia
Phone : 07 3451 1300
- **Further information obtainable from:** msds@motorex.com
- **Emergency telephone number:**
In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

- **Classification of the substance or mixture**
The product is not classified, according to the Globally Harmonised System (GHS).
- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- **Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1, H304	2.5-7.5%
CAS: 64742-65-0 EINECS: 265-169-7 Index number: 649-474-00-6	Distillates (petroleum), solvent-dewaxed heavy paraffinic Asp. Tox. 1, H304	≥0.25-≤2.5%

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations



Printing date 30.01.2024

Version number 3.1

Revision: 30.10.2023

Trade name: CROSS POWER 4T SAE 10W/50 JASO MA2

CAS: 85940-28-9 EINECS: 288-917-4	Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts Eye Dam. 1, H318; Skin Irrit. 2, H315	(Contd. of page 1) ≥0.25-<2.5%
--------------------------------------	---	-----------------------------------

Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346.
For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and Storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
The recommended storage temperature is (deg.C): ≤50°C
- **Storage class:** 10

(Contd. on page 3)

Trade name: CROSS POWER 4T SAE 10W/50 JASO MA2

(Contd. of page 2)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls and personal protection

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

Inhalative	DNEL	5.4 mg/m ³ /8h (worker)
	DNEL	1.2 mg/m ³ /24h (consumer)

· **Additional information:** The lists valid during the making were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

· **Body protection:** Protective work clothing

9 Physical and Chemical Properties

· **General Information**

· **Appearance:**

· **Form:**

Fluid

· **Colour:**

Brown

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/freezing point:**

Undetermined.

· **Initial boiling point and boiling range:** Undetermined.

· **Pouring point**

-43.6 °C

· **Flash point:**

>200 °C

· **Flammability (solid, gas):**

Not applicable.

· **Decomposition temperature:**

Not determined.

· **Explosive properties:**

Product does not present an explosion hazard.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations



Printing date 30.01.2024

Version number 3.1

Revision: 30.10.2023

Trade name: CROSS POWER 4T SAE 10W/50 JASO MA2

(Contd. of page 3)

· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.854 g/cm ³ (ASTM D 4052)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	111.8 mm ² /s @ 40 °C
· Solvent separation test:	
· VOC (EC)	0.00 %
· Other information	No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m ³ (rat)
	NOAEL	980 mg/m ³ (rat)

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations



Printing date 30.01.2024

Version number 3.1

Revision: 30.10.2023

Trade name: CROSS POWER 4T SAE 10W/50 JASO MA2

(Contd. of page 4)

Inhalative	LOAEL	1,000 mg/kg/24h (rabbit)
		100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m ³ (rat)
	NOAEL	980 mg/m ³ (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aquatic toxicity:

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)

- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**

· Bioaccumulative potential

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Partition coefficient	>6 [---] (log Kow) (Bioaccumulation)
-----------------------	--------------------------------------

64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

Partition coefficient	>6 [---] (log Kow) (Bioaccumulation)
-----------------------	--------------------------------------

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**

· General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations



Printing date 30.01.2024

Version number 3.1

Revision: 30.10.2023

Trade name: CROSS POWER 4T SAE 10W/50 JASO MA2

· **Other adverse effects** No further relevant information available.

(Contd. of page 5)

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· **ADG, ADN, IMDG, IATA**

Not classified as hazardous for transport

· **UN proper shipping name**

· **ADG, ADN, IMDG, IATA**

Not classified as hazardous for transport

· **Transport hazard class(es)**

· **ADG, ADN, IMDG, IATA**

· **Class**

Not classified as hazardous for transport

· **Packing group**

· **ADG, IMDG, IATA**

Not classified as hazardous for transport

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Not applicable.

· **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **UN "Model Regulation":**

Not classified as hazardous for transport

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Australian Inventory of Industrial Chemicals**

151006-63-2	1-Dodecene, homopolymer, hydrogenated
26401-35-4	DTDA
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic
85940-28-9	Phosphorodithioic acid, mixed O,O-bis(2-ethylhexyl and iso-Bu and iso-Pr) esters, zinc salts
128-39-2	2,6-di-tert-butylphenol
63148-62-9	Polydimethylsiloxane

(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations



Printing date 30.01.2024

Version number 3.1

Revision: 30.10.2023

Trade name: CROSS POWER 4T SAE 10W/50 JASO MA2

(Contd. of page 6)

540-97-6	Dodecamethylcyclohexasiloxane
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane
556-67-2	octamethylcyclotetrasiloxane

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· Directive 2012/18/EU
· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· purity requirement
· Relevant phrases

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Department issuing SDS: Abteilung Produktsicherheit

· Contact:
· Abbreviations and acronyms:

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· * Data compared to the previous version altered.

AU