MOTOREX\*
Oil of Switzerland
Revision: 25.10.2022

Printing date 30.01.2024

Version number 4.0

#### 1 Identification

- · Product identifier
- · Trade name: GREASE SPRAY
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Grease

Only for proper handling.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

**MOTOREX AG** 

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

### 2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms





GHS02 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics isopentane

Solvent naphtha (petroleum), heavy arom.

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

(Contd. on page 2)

MOTOREX Oil of Switzerland

Printing date 30.01.2024 Version number 4.0 Revision: 25.10.2022

Trade name: GREASE SPRAY

(Contd. of page 1)

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

### 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	25-50%
EC number: 918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Asp. Tox. 1, H304	10-25%
EC number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336	2.5-7.5%
CAS: 12001-85-3 EINECS: 234-409-2	zinc naphthenate Serious eye damage/irritation – Category 2A, H319; Skin Sens. 1B, H317	≥0.1-<0.25%
CAS: 68425-15-0 EINECS: 270-335-7	Polysulfides, di-tert-dodecyl Skin Sens. 1, H317	0.1-0.25%

# Regulation (EC) No 648/2004 on detergents / Labelling for contents aliphatic hydrocarbons ≥15 - <30%

#### 4 First Aid Measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Remove residues with soap and water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire Fighting Measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 30.01.2024 Version number 4.0 Revision: 25.10.2022

Trade name: GREASE SPRAY

(Contd. of page 2)

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

#### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and Storage

- Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- · Storage class: 2 B
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

Ingredients with limit values that require monitoring at the workplace:	
106-97-8 butane, pure	
WES Long-term value: 1900 mg/m³, 800 ppm	
74-98-6 propane	
WES Asphyxiant	
· DNELs	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics	

WES Asphyxiant			
·DNELs			
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics			
Oral	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)	
Dermal	DNEL / Workers / Systemic effects / Long- term	300 mg/kg/24h (worker)	
	DNEL/general population/Systemic effects/Long-term	300 mg/kg/24h (consumer)	
	•		(Contd. on page 4)

(Contd. on page 4

MOTOREX Oil of Switzerland
Revision: 25.10.2022

Printing date 30.01.2024

Version number 4.0

Trade name: GREASE SPRAY

		(Contd. of pa
Inhalative	DNEL / Workers / Systemic effects / Lon term	g-  1,500 mg/m3 (worker)
	DNEL/general population/System effects/Long-term	ic 900 mg/m3 (consumer)
12001-85	-3 zinc naphthenate	
Oral	DNEL/general population/System effects/Long-term	ic 0.00000017 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Long term	g- 3.3 mg/kg/24h (worker)
	DNEL/general population/System effects/Long-term	ic 1.7 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long term	g- 1.18 mg/m3 (worker)
	DNEL/general population/System effects/Long-term	ic 0.29 mg/m3 (consumer)
68425-15	-0 Polysulfides, di-tert-dodecyl	
Oral	DNEL/general population/System effects/Long-term	ic 1.66 mg/kg/24h (consumer)
Dermal	DNEL / Workers / Systemic effects / Longterm	g- 33.3 mg/kg/24h (worker)
	DNEL/general population/System effects/Long-term	ic 16.66 mg/kg/24h (consumer)
Inhalative	DNEL / Workers / Systemic effects / Long term	g- 23.5 mg/m3 (worker)
	DNEL/general population/System effects/Long-term	ic 5.8 mg/m3 (consumer)
PNECs		•
12001-85	-3 zinc naphthenate	
PNE	EC / Aquatic organisms / Freshwater	0.004 mg/l (aquatic organisms)
PNE	EC / Aquatic organisms / Marine water	0.0004 mg/l (aquatic organisms)
PN	EC/Aquatic org/intermittent ases(freshwater)	- · · · · · · · · · · · · · · · · · · ·
	EC/Aquatic organisms/Sewage treatment	0.6897 mg/l (aquatic organisms)
PNI	EC / Aquatic organisms / Sediment shwater)	0.015-19.438 mg/kg (aquatic organisms)
	EC / Aquatic organisms / Sediment rine water)	0.0015-1.9438 mg/kg (aquatic organisms)
68425-15	-0 Polysulfides, di-tert-dodecyl	
	EC / Predators / Secondary poisoning	66.7 mg/kg food (secondary poisoni (predators))
	EC/Aquatic organisms/Sewage treatment	1,000 mg/l (aquatic organisms)

- · Additional information: The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

(Contd. on page 5)

MOTOREX Oil of Switzerland

Printing date 30.01.2024 Version number 4.0 Revision: 25.10.2022

Trade name: GREASE SPRAY

(Contd. of page 4)

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Not required.
- · Body protection: Protective work clothing

### 9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Liquefied gas
Colour: Yellowish
Odour: Solvent-like
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: Not applicable, as aerosol.

Flash point:
 Flammability (solid, gas):
 Decomposition temperature:
 Not applicable.
 Not determined.

Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.

• **Density at 20 °C:** 0.645 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

· water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Other information No further relevant information available.

### 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)



Printing date 30.01.2024

Version number 4.0

Trade name: GREASE SPRAY

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values relevan	t for classification:
106-97-8 L	butane, pure	
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)
	LC50 / 15 min	800,000 ppm (rat)
	LC50 / 2h	1,237 mg/l (mouse)
	LC50 / 2h	520,400-539,600 ppm (mouse)
	LC50 / 4h	658 mg/l (rat)
	NOAEC	4,000-16,000 ppm (rat)
	NOAEC	7.2-21.4 mg/l (rat)
	LOAEC	21.6 mg/l (rat)
	LOAEC	12,000 ppm (rat)
Hydrocar	bons, C9-C11,	n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
Oral	LD50	5,000-15,000 mg/kg (rat)
	NOAEL	1,000-5,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
		3,160-5,000 mg/kg (rabbit)
Inhalative	LC50 / 4h	4.951-9.3 mg/l (rat)
	LC50 / 8h	41-4,467 ppm (rat)
	LC50 / 8h	5 mg/l (rat)
	NOAEL	200 ppm (rat)
	NOAEC	275-10,400 mg/m3 (rat)
12001-85-	3 zinc naphthe	enate
Oral	LD50	2,000 ml/kg (rat)
	NOAEL	13.26-900 mg/kg/24h (rat)
68425-15-	0 Polysulfides	, di-tert-dodecyl
Oral	LD50	19,550 mg/kg (rat)
	NOAEL	1,000 mg/kg/24h (rat)
Dermal	LD50	2,000 mg/kg (rat)
Inhalative	LC50 / 4h	15.5 mg/l (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard May be fatal if swallowed and enters airways.

MOTOREX\*
Oil of Switzerland
Revision: 25.10.2022

Printing date 30.01.2024

Version number 4.0

Trade name: GREASE SPRAY

(Contd. of page 6)

## 12 Ecological Information

#### · Toxicity

· Aquatic	
_	B butane, pure
LC50	24.1-147.5 mg/l/96h (fish)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)
Hydroca	arbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics
LL50	1,000 mg/l/96h (fish)
LL50	1,000 mg/l/72h (fish)
LL50	1,000 mg/l/48h (fish)
LL50	1,000 mg/l/24h (fish)
LL0	100 mg/l/96h (fish)
EL50	1,000 mg/l/48h (aquatic invertebrates)
EL50	1,000 mg/l/24h (aquatic invertebrates)
EL50	1,000 mg/l/72h (algae / cyanobacteria)
EL0	1,000 mg/l/48h (aquatic invertebrates)
NOELR	0.131 mg/l/28d (fish)
NOELR	0.23 mg/l/21d (aquatic invertebrates)
NOELR	3-100 mg/l/72h (algae / cyanobacteria)
12001-8	5-3 zinc naphthenate
LC50	1.53-2 ppm/96h (Lepomis macrochirus)
EC50	4.6 ppm/48h (Daphnia Magna)
EC50	5.2 mg/l/3h (microorganisms)
LL50	100 mg/l/96h (fish)
EL50	35 mg/l/48h (aquatic invertebrates)
EL50	1.4-4 mg/l/72h (algae / cyanobacteria)
NOELR	0.32-1 mg/l/72h (algae / cyanobacteria)
68425-1	5-0 Polysulfides, di-tert-dodecyl
LC50	100 mg/l/96h (fish)
LC0	100 mg/l/96h (fish)
LL50	100 mg/l/96h (fish)
NOEC	0.08 mg/l/72h (algae / cyanobacteria)
	10-10,000 mg/l/72h (microorganisms)
NOEC	100 mg/l/96h (fish)
NOEC	0.1 mg/l/48h (aquatic invertebrates)

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:

· Bioaccumulative p	· Bioaccumulative potential		
106-97-8 butane, p	106-97-8 butane, pure		
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)		
Hydrocarbons, C9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cycloalkanes, <2% aromatics		
Biodegradability	80 % (28d) (Bioaccumulation) (OECD 301 F)		
68425-15-0 Polysu	68425-15-0 Polysulfides, di-tert-dodecyl		
Partition coefficient	6.2-12.45 [] (log Kow) (Bioaccumulation)		

• Mobility in soil No further relevant information available.

(Contd. on page 8)

MOTOREX\*
Oil of Switzerland

Revision: 25.10.2022

Printing date 30.01.2024 Version number 4.0

Trade name: GREASE SPRAY

(Contd. of page 7)

- · Additional ecological information:
- General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

### 14 Transport information

· UN-Number

· **ADG, IMDG, IATA** UN1950

· UN proper shipping name

• ADG 1950 AEROSOLS • IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · Transport hazard class(es)
- · ADG



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· Packing group

· ADG, IMDG, IATA Not classified as hazardous for transport

(Contd. on page 9)

Revision: 25.10.2022

Version number 4.0 Printing date 30.01.2024

Trade name: GREASE SPRAY

	(Contd. of page
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Gases.
Hazard identification number (Kemler of	code): -
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WAST AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex I. Marpol and the IBC Code	l of Not applicable.
Transport/Additional information:	
ADG	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
	1L
IMDG	1L Code: E0
IMDG Limited quantities (LQ)	

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

111111111111111111111111111111111111111	
Australian	Inventory of Industrial Chemicals
106-97-8	B butane, pure
74-98-6	propane
75-28-5	isobutane
78-78-4	isopentane
	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)
12001-85-3	zinc naphthenate
68425-15-0	Polysulfides, di-tert-dodecyl
64742-94-5	Solvent naphtha (petroleum), heavy arom.
29190-28-1	2,4-bis(xylylazo)resorcinol
	(Contd. on page 10)

(Contd. on page 10)

MOTOREX Oil of Switzerland
Revision: 25.10.2022

Printing date 30.01.2024

Version number 4.0

Trade name: GREASE SPRAY

	(Contd. of page 9)
91-20-3 naphthalene	
· Standard for the Uniform Scheduling of Medicines and Poisons	
91-20-3 naphthalene	S6, S10
· Australia: Priority Existing Chemicals	
None of the ingredients is listed.	

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National chemical directories

Components listed or exempted from listing:

TSCA (USA) DSL/NDSL (CDN)

AICS (Aus) IECSC (CN)

EINECS/ELINCS/NLP (EU)

ECL/KECI (KOR)

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

#### · purity requirement

#### Relevant phrases

H220 Extremely flammable gas.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Abteilung Produktsicherheit
- Contact:

#### · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Serious eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.

ΔΗ