MOTOREX*
Oil of Switzerland
Revision: 13.03.2023

Printing date 30.01.2024

Version number 2.1

1 Identification

- · Product identifier
- · Trade name: KTM RACING 4T SAE 20W/60
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Engine oil

Only for proper handling.

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- Signal word Void
- · Hazard statements Void
- · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	Dangerous	components:
--	------------------	-------------

CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic 2.5-7.5% EINECS: 265-157-1 Asp. Tox. 1, H304 Index number: 649-467-00-8

(Contd. on page 2)



Printing date 30.01.2024 Version number 2.1 Revision: 13.03.2023

Trade name: KTM RACING 4T SAE 20W/60

	(0	Contd. of page 1)
	Mineral oils (mixture)	≥2.5-≤7.5%
	Asp. Tox. 1, H304	
CAS: 84605-29-8 EINECS: 283-392-8	Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc salts	≥1-<2.5%
	Eye Dam. 1, H318; Skin Irrit. 2, H315	
EC number: 947-519-7	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. Para-, calcium salts Skin Sens. 1B, H317	≥0.1-≤1%

Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

· After eve contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: DO NOT USE WATER JET
- · Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and phosphorus oxides can be formed.

· Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 3)

MOTOREX Oil of Switzerland
Revision: 13.03.2023

Printing date 30.01.2024

Version number 2.1

Trade name: KTM RACING 4T SAE 20W/60

(Contd. of page 2)

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap. No special measures required.

- · Information about fire and explosion protection: Do not heat above flash point.
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Store containers closed and protect against rain, dust, heat and other atmospheric influences.

- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

0400	J-2 9 -	8 Phosphorodithioic acid, mixed O,O salts	·DIS (1,3-aieti	nyibutyi and iso-Prjesters, zii
Oral		DNEL/general population/Systemic effect	ts/Long-term	0.24 mg/kg/24h (consumer)
Dermal Inhalative		DNEL / Workers / Systemic effects / Long-term		12.1 mg/kg/24h (worker)
		DNEL/general population/Systemic effect	6.1 mg/kg/24h (consumer)	
		DNEL / Workers / Systemic effects / London	8.31 mg/m3 (worker)	
		DNEL/general population/Systemic effect	2.11 mg/m3 (consumer)	
PNE	Cs			
8460	5-29-	8 Phosphorodithioic acid, mixed O,O salts	-bis (1,3-diet	hylbutyl and iso-Pr)esters, zi
		0/5 / 1 / 0 / 1 / 1		
Oral	PNE	C / Predators / Secondary poisoning	10.67 mg/k (predators))	rg food (secondary poisoni
		C / Predators / Secondary poisoning C / Aquatic organisms / Freshwater	(predators))	rg food (secondary poisonii aquatic organisms)
	PNE	, ,	(predators)) 0.004 mg/l (a	rg food (secondary poisoni aquatic organisms) (aquatic organisms)
	PNE PNE P N E	C / Aquatic organisms / Freshwater	(predators)) 0.004 mg/l (a 0.0046 mg/l	aquatic organisms)
	PNE PNE P N E relea PNE	C / Aquatic organisms / Freshwater C / Aquatic organisms / Marine water E C / A q u a t i c o r g / i n t e r m i t t e n t	(predators)) 0.004 mg/l (a 0.0046 mg/l 0.045 mg/l (a	aquatic organisms) (aquatic organisms) aquatic organisms)
	PNE PNE PNE relea PNE plant PNE	C / Aquatic organisms / Freshwater C / Aquatic organisms / Marine water E C / A q u a t i c o r g / i n t e r m i t t e n t ses(freshwater) C/Aquatic organisms/Sewage treatment	(predators)) 0.004 mg/l (a 0.0046 mg/l (a 0.045 mg/l (a 100 mg/l (aq	aquatic organisms) (aquatic organisms) aquatic organisms) uatic organisms)
	PNE PNE PNE relea PNE plant PNE (fresi	C / Aquatic organisms / Freshwater C / Aquatic organisms / Marine water E C / A q u a t i c o r g / i n t e r m i t t e n t ses(freshwater) C/Aquatic organisms/Sewage treatment /STP C / Aquatic organisms / Sediment	(predators)) 0.004 mg/l (a 0.0046 mg/l (a 0.045 mg/l (a 100 mg/l (aq 0.02203 mg/l	equatic organisms) (aquatic organisms) equatic organisms) uatic organisms) kg (aquatic organisms)

Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

MOTOREX Oil of Switzerland

Printing date 30.01.2024 Version number 2.1 Revision: 13.03.2023

Trade name: KTM RACING 4T SAE 20W/60

(Contd. of page 3)

· Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Fluid
Colour: Dark yellow
Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

Melting point/freezing point:
Initial boiling point and boiling range:
Flash point:
Flammability (solid, gas):
Auto-ignition temperature:
Decomposition temperature:

Undetermined.

>200 °C
Not applicable.
255 °C (DIN 51794)
Not determined.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.

• **Density at 20 °C:** 0.863 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

Partition coefficient: n-octanol/water: Not determined.
Viscosity: 168.3 mm2/s @ 40 °C
Dynamic: Not determined.
Kinematic: 168.3 mm²/s @ 40 °C

(Contd. on page 5)

MOTOREX*
Oil of Switzerland
Revision: 13.03,2023

Printing date 30.01.2024

Version number 2.1

Trade name: KTM RACING 4T SAE 20W/60

Solvent separation test:
 VOC (EC)
 Other information
 No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:					
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic					
Oral	Oral LD50 5,000 mg/kg (rat)				
	LOAEL	125 mg/kg/24h (rat)			
Dermal	LD50	2,000-5,000 mg/kg (rabbit)			
	NOAEL	150 mg/kg/24h (mouse)			
		30-2,000 mg/kg/24h (rat)			
		1,000 mg/kg/24h (rabbit)			
	LOAEL	100 mg/kg/24h (mouse)			
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)			
	NOEL	220 mg/m3 (rat)			
	NOAEL	980 mg/m3 (rat)			
84605-29-8 Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc					
	salts				
Oral	NOEL	40 mg/kg/24h (rat)			
	NOAEL	160 mg/kg/24h (rat)			
Dermal	LD50	2,002 mg/kg (rat)			
Inhalative	LC50 / 4h	2.3 mg/l (rat)			

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

AU

MOTOREX*
Oil of Switzerland
Revision: 13.03.2023

Printing date 30.01.2024

Version number 2.1

Trade name: KTM RACING 4T SAE 20W/60

(Contd. of page 5)

12 Ecological Information

· Toxicity

· Aquatic	Aquatic toxicity:					
64742-5	64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic					
LL50	LL50 10,000 mg/l/96h (aquatic invertebrates)					
	100 mg/l/96h (fish)					
LL50	10,000 mg/l/72h (aquatic invertebrates)					
LL50	10,000 mg/l/48h (aquatic invertebrates)					
LL50	10,000 mg/l/24h (aquatic invertebrates)					
EL50	10,000 mg/l/48h (aquatic invertebrates)					
84605-2	84605-29-8 Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc					
	salts					
LOEC	0.8 mg/l/21d (aquatic invertebrates)					
LC50	46 mg/l/96h (fish)					
EC50	10,000 mg/l/3h (microorganisms)					
LL50	4.5 mg/l/96h (fish)					
EL50						
EL50	EL50 21-24 mg/l/72h (algae / cyanobacteria)					
NOEC	NOEC 0.4-0.8 mg/l/21d (aquatic invertebrates)					
NOELR	NOELR 1.8 mg/l/96h (fish)					
NOELR	10 mg/l/48h (aquatic invertebrates)					
Reactio	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. Para-,					
calcium	salts					
LC50	>1,000 mg/l/96h (Pimephales promelas)					
	>100 mg/l/96h (rainbow trout)					
EC50	>1,000 mg/l/96h (algae)					

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Partition coefficient >6 [---] (log Kow) (Bioaccumulation)

84605-29-8 Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc salts

Partition coefficient 0.56 [---] (log Kow) (Bioaccumulation)

- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

ΑU

MOTOREX Oil of Switzerland
Revision: 13.03.2023

Printing date 30.01.2024 Version number 2.1

Trade name: KTM RACING 4T SAE 20W/60

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number · ADG, ADN, IMDG, IATA	Not classified as hazardous for transport
· UN proper shipping name · ADG, ADN, IMDG, IATA	Not classified as hazardous for transport
· Transport hazard class(es)	
· ADG, ADN, IMDG, IATA · Class	Not classified as hazardous for transport
· Packing group · ADG, IMDG, IATA	Not classified as hazardous for transport
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
· UN "Model Regulation":	Not classified as hazardous for transport

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals		
	DURASYN 128	
26401-35-4	DTDA	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc salts	
36878-20-3	Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	
	diphenylamine	
108-31-6	maleic anhydride	

· Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

(Contd. on page 8)

MOTOREX*
Oil of Switzerland
Revision: 13.03.2023

Printing date 30.01.2024

Version number 2.1

Trade name: KTM RACING 4T SAE 20W/60

(Contd. of page 7)

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- · Relevant phrases

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Contact:
- · Abbreviations and acronyms:

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

Δ11