MOTOREX*
Oil of Switzerland
Revision: 08.01,2024

Printing date 30.01.2024

Version number 2.0

1 Identification

- · Product identifier
- · Trade name: MOTO SHINE MS 1
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture

Only for proper handling. detergent

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG Bern–Zürich–Strasse 31, Postfach CH–4901 Langenthal Tel. +41 (0)62 919 75 75 www.motorex.com

A1 Accessory Imports 60-62 Burchill St. Loganholme 4129 QLD Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol.

Pressurised container: May burst if

heated.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters

airways.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

propan-2-ol

isopentane

Caryophyllene

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)



Printing date 30.01.2024 Version number 2.0 Revision: 08.01.2024

Trade name: MOTO SHINE MS 1

(Contd. of page 1)

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	≥25-≤50%
	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	25-50%
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; STOT SE 3, H336	≥20-<25%

Regulation (EC) No 648/2004 on detergents / Labelling for contents			
aliphatic hydrocarbons	≥15 - <30%		
perfumes (CINNAMAL, Eugenol)	<5%		

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

AU

MOTOREX Oil of Switzerland
Revision: 08.01.2024

Printing date 30.01.2024

Version number 2.0

Trade name: MOTO SHINE MS 1

(Contd. of page 2)

5 Fire Fighting Measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- Storage class: 2 B
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

WES Short-term value: 1230 mg/m³, 500 ppm Long-term value: 983 mg/m³, 400 ppm

106-97-8 butane, pure

WES Long-term value: 1900 mg/m³, 800 ppm

(Contd. on page 4)

MOTOREX Oil of Switzerland
Revision: 08.01.2024

Printing date 30.01.2024

Version number 2.0

Trade name: MOTO SHINE MS 1

74.00.6	240000		(Contd. of page		
74-98-6	-				
	S Asphyxiant				
DNELs					
	propan-2-ol				
Oral	DNEL/general population/Systemic effect	•	26 mg/kg/24h (consumer)		
Dermal	DNEL / Workers / Systemic effects / Long	•	888 mg/kg/24h (worker)		
	DNEL/general population/Systemic effect	ts/Long-term	319 mg/kg/24h (consumer)		
Inhalative	e DNEL / Workers / Systemic effects / Lon	g-term	500 mg/m3 (worker)		
	DNEL/general population/Systemic effec	ts/Long-term	89 mg/m3 (consumer)		
Hydroca	rbons, C7-C9, n-alkanes, isoalkanes, cy	clics			
Oral	DNEL/general population/Systemic effec	ts/Long-term	699 mg/kg/24h (consumer)		
Dermal	DNEL / Workers / Systemic effects / Long	g-term	773 mg/kg/24h (worker)		
	DNEL/general population/Systemic effect	ts/Long-term	699 mg/kg/24h (consumer)		
Inhalative	DNEL / Workers / Systemic effects / Lon	g-term	2,035 mg/m3 (worker)		
	DNEL/general population/Systemic effec	ts/Long-term	608 mg/m3 (consumer)		
PNECs					
-	propan-2-ol				
Oral PN	EC / Predators / Secondary poisoning	160 mg/kg (predators))	ı food (secondary poisonin		
PN	EC / Aquatic organisms / Freshwater	140.9 mg/l (a	aquatic organisms)		
PN	EC / Aquatic organisms / Marine water	140.9 mg/l (á	aquatic organisms)		
	PNEC/Aquatic org/intermittent releases(freshwater) PNEC/Aquatic organisms/Sewage treatment plant/STP		aquatic organisms)		
			aquatic organisms)		
	EC / Aquatic organisms / Sediment shwater)	552 mg/kg (a	aquatic organisms)		
PN	EC / Aquatic organisms / Sediment arine water)	552 mg/kg (a	aquatic organisms)		
DN	EC / Terrestrial organism / Soil	28 ma/ka (te	rrestrial organisms)		

- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore (Contd. on page 5)



Printing date 30.01.2024 Version number 2.0 Revision: 08.01.2024

Trade name: MOTO SHINE MS 1

(Contd. of page 4)

to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

· Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Aerosol
Colour: Colourless
Odour: cherry

· Odour threshold: Not determined. · pH-value: Not determined.

· Change in condition

· Melting point/freezing point: Undetermined.

· Initial boiling point and boiling range: Not applicable, as aerosol.

Flash point:
 Flammability (solid, gas):
 Decomposition temperature:
 Not applicable.
 Not determined.

• Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.

• **Density at 20 °C:** 0.688 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent separation test:

· **VOC (EC)** 89.10 %

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

AU

MOTOREX Oil of Switzerland
Revision: 08.01.2024

Printing date 30.01.2024

Version number 2.0

Trade name: MOTO SHINE MS 1

(Contd. of page 5)

11 Toxicological Information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:				
67-63-0 pi	67-63-0 propan-2-ol			
Oral	LD50	5,840 mg/kg (rat)		
Dermal	LD50	16.4 ml/kg (rabbit)		
	LD50	12,800 mg/kg (rabbit)		
Inhalative	LC50 / 6h	10,000 ppm (rat)		
	NOAEC	5,000 ppm (rat)		
	NOEC	500-5,000 ppm (rat)		
106-97-8	butane, pure			
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)		
	LC50 / 15 min	800,000 ppm (rat)		
	LC50 / 2h	1,237 mg/l (mouse)		
	LC50 / 2h	520,400-539,600 ppm (mouse)		
	LC50 / 4h	658 mg/l (rat)		
	NOAEC	4,000-16,000 ppm (rat)		
	NOAEC	7.2-21.4 mg/l (rat)		
	LOAEC	21.6 mg/l (rat)		
	LOAEC	12,000 ppm (rat)		
Hydrocari	bons, C7-C9, n	-alkanes, isoalkanes, cyclics		
Oral	LD50	8 ml/kg (rat)		
Dermal	LD50	4 ml/kg (rat)		
	LD50	2,800-3,100 mg/kg (rat)		
Inhalative	LC50 / 4h	23.3 mg/l (rat)		
	NOAEC	5.8-24.3 mg/l (rat)		

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

12 Ecological Information

· Toxicity

· Aquati	· Aquatic toxicity:		
67-63-0	O propan-2-ol		
LC50	9.64-10 mg/l/96h (fish)		
LC50	10,000 mg/l/24h (aquatic invertebrates)		
EC50	10,000 mg/l/24h (aquatic invertebrates)		
106-97	106-97-8 butane, pure		
LC50	24.1-147.5 mg/l/96h (fish)		
	(Contd. on page 7)		

(Contd. on page 7)

MOTOREX Oil of Switzerland
Revision: 08.01.2024

Printing date 30.01.2024

Version number 2.0

Trade name: MOTO SHINE MS 1

		(Contd. of page 6)
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)	
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)	
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
EC50	0.23 mg/l/21d (aquatic invertebrates)	
EC50	0.64 mg/l/48h (aquatic invertebrates)	
LL50	3-10 mg/l/96h (fish)	
LL50	10-30 mg/l/72h (fish)	
LL50	10-30 mg/l/48h (fish)	
LL50	30-100 mg/l/24h (fish)	
LL0	3 mg/l/96h (fish)	
EL50	13 mg/l/96h (algae / cyanobacteria)	
EL50	4.6-10 mg/l/48h (aquatic invertebrates)	
	10-30 mg/l/48h (algae / cyanobacteria)	
EL50	10-22 mg/l/24h (aquatic invertebrates)	
	10-30 mg/l/24h (algae / cyanobacteria)	
EL50	10-30 mg/l/72h (algae / cyanobacteria)	
EL0	4.6 mg/l/48h (aquatic invertebrates)	
EL0	10 mg/l/24h (aquatic invertebrates)	
NOEC	0.17 mg/l/21d (aquatic invertebrates)	
NOELR	0.574 mg/l/28d (fish)	
NOELR	1 mg/l/21d (aquatic invertebrates)	
NOELR	6.3 mg/l/96h (algae / cyanobacteria)	
LOEC	0.32 mg/kg/28d (aquatic invertebrates)	

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:

· Bioaccumulative potential			
67-63-0 propan-2-c	ol .		
Partition coefficient	0.05 [] (log Kow) (Bioaccumulation)		
Biodegradability	>70 % (28d) (Biodegradability) (EU Method C.5)		
106-97-8 butane, p	106-97-8 butane, pure		
Partition coefficient 1.09-2.8 [] (log Kow) (Bioaccumulation)			
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Biodegradability	98 % (28d) (Biodegradability) (OECD 301 F)		

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

MOTOREX*
Oil of Switzerland
Revision: 08.01.2024

Printing date 30.01.2024 Version number 2.0

Trade name: MOTO SHINE MS 1

(Contd. of page 7)

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

f	
14	
7	
ra	
n	
30	
0	
rt	
71	
ก	
Ю	
ri	
n	
ai	
П	
0	
î	

· UN-Number	
ADG IMDG IATA	LIN11050

· **ADG, IMDG, IATA** UN1950

· UN proper shipping name · ADG 1950 A

· ADG 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

· Transport hazard class(es)

· ADG



· Class 2 5F Gases.

· **Label** 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· Packing group

· ADG, IMDG, IATA Not classified as hazardous for transport

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code): ·

· EMS Number: F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE

AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 9)

- AU

MOTOREX Oil of Switzerland
Revision: 08.01.2024

Printing date 30.01.2024 Version number 2.0

Trade name: MOTO SHINE MS 1

	(Contd. of page 8
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADG Limited quantities (LQ) Excepted quantities (EQ) Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
Tunnel restriction code	D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	nventory of Industrial Chemicals
	propan-2-ol
106-97-8	butane, pure
63148-62-9	Polydimethylsiloxane
74-98-6	propane
63148-62-9	Polydimethylsiloxane
<i>75-28-5</i>	isobutane
78-78-4	isopentane
100-52-7	benzaldehyde
123-92-2	isopentyl acetate
104-55-2	Cinnamal
97-53-0	Eugenol
104-67-6	5-heptyloxolan-2-one
106-27-4	Isoamyl butyrate
106-30-9	Ethyl heptanoate
121-32-4	3-ethoxy-4-hydroxybenzaldehyde
87-44-5	Caryophyllene
5989-27-5	(R)-p-mentha-1,8-diene
98-01-1	2-furaldehyde
	(Contd. on page 1

AU



Printing date 30.01.2024

Version number 2.0

Trade name: MOTO SHINE MS 1

(Contd. of page 9)

Standard for the Uniform Scheduling of Medicines and Poisons			
97-53-0	Eugenol	S5, S6	
98-01-1	2-furaldehyde	<i>S6</i>	

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Contact:
- · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Serious eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.

- AU