MOTOREX
Oil of Switzerland
Revision: 21.11.2023

Printing date 30.01.2024

Version number 1.0

1 Identification

- · Product identifier
- · Trade name: POWER CLEAN SPRAY
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Cleaning material/ Detergent Only for proper handling.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- · GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics isopentane

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

(Contd. on page 2)

MOTOREX Oil of Switzerland

Printing date 30.01.2024 Version number 1.0 Revision: 21.11.2023

Trade name: POWER CLEAN SPRAY

(Contd. of page 1)

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; STOT SE 3, H336	50-70%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane, pure Flam. Gas 1, H220; Press. Gas C, H280	25-50%
· Regulation (EC) No 648/200	4 on detergents / Labelling for contents	
aliphatic hydrocarbons		≥30%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 3)

MOTOREX*
Oil of Switzerland

Revision: 21.11.2023

Printing date 30.01.2024 Version number 1.0

Trade name: POWER CLEAN SPRAY

(Contd. of page 2)

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Keep container tightly sealed.

- Storage class: 2 B
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredien	· Ingredients with limit values that require monitoring at the workplace:		
106-97-8 k	106-97-8 butane, pure		
WES Long	WES Long-term value: 1900 mg/m³, 800 ppm		
74-98-6 pi	74-98-6 propane		
WES Asp	WES Asphyxiant		
· DNELs	DNELs		
Hydrocari	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)	
Dermal	DNEL / Workers / Systemic effects / Long-term	773 mg/kg/24h (worker)	
	DNEL/general population/Systemic effects/Long-term	699 mg/kg/24h (consumer)	
Inhalative	DNEL / Workers / Systemic effects / Long-term	2,035 mg/m3 (worker)	
	DNEL/general population/Systemic effects/Long-term	608 mg/m3 (consumer)	

- · Additional information: The lists valid during the making were used as basis.
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

(Contd. on page 4)



Printing date 30.01.2024 Version number 1.0 Revision: 21.11.2023

Trade name: POWER CLEAN SPRAY

(Contd. of page 3)

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Not required.
- · Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Liquefied gas
Colour: Colourless
Odour: Petrol-like
Odour threshold: Not determined.
pH-value: Not determined.

· Change in condition

· **Melting point/freezing point:** Undetermined.

· Initial boiling point and boiling range: Not applicable, as aerosol.

Flash point: <-20 °C
 Flammability (solid, gas): Not applicable.
 Decomposition temperature: Not determined.

Explosive properties: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

Lower: Not determined.
 Upper: Not determined.
 Vapour pressure: Not determined.

• **Density at 20 °C:** 0.72 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not applicable.

· Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent separation test:

· **VOC (EC)** 100.00 %

· Other information No further relevant information available.

ΔΠ

MOTOREX
Oil of Switzerland
Revision: 21.11.2023

Printing date 30.01.2024 Version number 1.0

Trade name: POWER CLEAN SPRAY

(Contd. of page 4)

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:		
Hydrocari	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		
Oral	LD50	8 ml/kg (rat)	
Dermal	LD50	4 ml/kg (rat)	
	LD50	2,800-3,100 mg/kg (rat)	
Inhalative	LC50 / 4h	23.3 mg/l (rat)	
	NOAEC	5.8-24.3 mg/l (rat)	
106-97-8	butane, pure		
Inhalative	LC50 / 15 min	1,442.738-1.443 mg/l (rat)	
	LC50 / 15 min	800,000 ppm (rat)	
	LC50 / 2h	1,237 mg/l (mouse)	
	LC50 / 2h	520,400-539,600 ppm (mouse)	
	LC50 / 4h	658 mg/l (rat)	
	NOAEC	4,000-16,000 ppm (rat)	
	NOAEC	7.2-21.4 mg/l (rat)	
	LOAEC	21.6 mg/l (rat)	
	LOAEC	12,000 ppm (rat)	

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · **Aspiration hazard** May be fatal if swallowed and enters airways.

12 Ecological Information

· Toxicity

· Aquatio	· Aquatic toxicity:		
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
EC50	0.23 mg/l/21d (aquatic invertebrates)		
EC50	0.64 mg/l/48h (aquatic invertebrates)		
LL50	3-10 mg/l/96h (fish)		

(Contd. on page 6)

MOTOREX*
Oil of Switzerland

Revision: 21.11.2023

Printing date 30.01.2024

Version number 1.0

Trade name: POWER CLEAN SPRAY

	(Contd. of page 5)	
LL50	10-30 mg/l/72h (fish)	
LL50	10-30 mg/l/48h (fish)	
LL50	30-100 mg/l/24h (fish)	
LL0	3 mg/l/96h (fish)	
EL50	13 mg/l/96h (algae / cyanobacteria)	
EL50	4.6-10 mg/l/48h (aquatic invertebrates)	
	10-30 mg/l/48h (algae / cyanobacteria)	
EL50	10-22 mg/l/24h (aquatic invertebrates)	
	10-30 mg/l/24h (algae / cyanobacteria)	
EL50	10-30 mg/l/72h (algae / cyanobacteria)	
EL0	4.6 mg/l/48h (aquatic invertebrates)	
EL0	10 mg/l/24h (aquatic invertebrates)	
NOEC	0.17 mg/l/21d (aquatic invertebrates)	
NOELR	0.574 mg/l/28d (fish)	
NOELR	1 mg/l/21d (aquatic invertebrates)	
NOELR	6.3 mg/l/96h (algae / cyanobacteria)	
LOEC	0.32 mg/kg/28d (aquatic invertebrates)	
106-97-8	106-97-8 butane, pure	
LC50	24.1-147.5 mg/l/96h (fish)	
LC50	14.2-69.4 mg/l/48h (aquatic invertebrates)	
EC50	7.7-19.4 mg/l/96h (algae / cyanobacteria)	

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:

· Bioaccumulative p	· Bioaccumulative potential	
Hydrocarbons, C7	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	
Biodegradability	98 % (28d) (Biodegradability) (OECD 301 F)	
106-97-8 butane, p	106-97-8 butane, pure	
Partition coefficient	1.09-2.8 [] (log Kow) (Bioaccumulation)	

- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

(Contd. on page 7)

MOTOREX Oil of Switzerland
Revision: 21.11.2023

Printing date 30.01.2024

Version number 1.0

Trade name: POWER CLEAN SPRAY

(Contd. of page 6)

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

Transport information	
UN-Number ADG, IMDG, IATA	UN1950
UN proper shipping name ADG	1950 AEROSOLS, ENVIRONMENTAL HAZARDOUS
IMDG IATA	AEROSOLS, MARINE POLLUTANT AEROSOLS, flammable
Transport hazard class(es)	
ADG	
Y 2	
· Class · Label	2 5F Gases. 2.1
·IMDG	
· Class · Label	2.1 Gases. 2.1
IATA	
Class Label	2.1 Gases. 2.1
Packing group ADG, IMDG, IATA	Not classified as hazardous for transport
Environmental hazards:	Product contains environmentally hazardo substances: Hydrocarbons, C7-C9, n-alkan isoalkanes, cyclics
Marine pollutant: Special marking (ADG):	Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user Hazard identification number (Keml	Warning: Gases. ler code): -
EMS Number:	F-D,S-U

(Contd. on page 8)

MOTOREX Oil of Switzerland

Printing date 30.01.2024 Version number 1.0 Revision: 21.11.2023

Trade name: POWER CLEAN SPRAY

	(Contd. of page
· Stowage Code · Segregation Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacit of 1 litre: Category A. For AEROSOLS with capacity above 1 litre: Category B. For WASTI AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacit of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	1L Code: E0 Not permitted as Excepted Quantity 2 D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

	IIIIXluie			
	· Australian Inventory of Industrial Chemicals			
Ī	106-97-8	butane, pure		
Ī	74-98-6	propane		
Ī	75-28-5	isobutane		
	78-78-4	isopentane		
Ī	Standard for the Uniform Scheduling of Medicines and Poisons			
Ī	None of the ingredients is listed.			
Ī	· Australia: Priority Existing Chemicals			
Ī	None of th	he ingredients is listed.		

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- P3a FLAMMABLE AEROSOLS
- E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 9)

MOTOREX*
Oil of Switzerland
Revision: 21.11.2023

Printing date 30.01.2024

Version number 1.0

Trade name: POWER CLEAN SPRAY

(Contd. of page 8)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Contact:
- · Abbreviations and acronyms:

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

AU