MOTOREX\*
Oil of Switzerland

Revision: 01.02.2022

Printing date 30.01.2024

Version number 2.3

### 1 Identification

- · Product identifier
- · Trade name: PRISMA ZX SAE 75W/90
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Gear Oil

Only for proper handling.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

**MOTOREX AG** 

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

## 2 Hazard(s) Identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT:

255881-94-8 Alkyl dithiophosphate

· vPvB: Not applicable.

## 3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated	25-50%
EINECS: 276-738-4	neutral oil-based	
Index number: 649-483-00-5	Asp. Tox. 1, H304	

(Contd. on page 2)



Printing date 30.01.2024 Version number 2.3

Trade name: PRISMA ZX SAE 75W/90

	(0	Contd. of page 1)
	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1, H304	2.5-7.5%
	Distillates (petroleum), solvent-dewaxed heavy paraffinic Asp. Tox. 1, H304	≥0.1-≤7.5%
	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1, H304	≥0-≤7.5%
	Distillates (petroleum), solvent-dewaxed light paraffinic Asp. Tox. 1, H304	≥0-≤7.5%
ELINCS: 401-850-9	Alkyl dithiophosphate Repr. 2, H361 PBT	≥0.25-≤1%

#### ·SVHC

255881-94-8 Alkyl dithiophosphate

#### · Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

## 4 First Aid Measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire Fighting Measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and nitrogen oxides can be formed.

· Protective equipment: No special measures required.

### 6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

MOTOREX
Oil of Switzerland
Revision: 01.02.2022

Printing date 30.01.2024 Version number 2.3

Trade name: PRISMA ZX SAE 75W/90

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap. No special measures required.

- · Information about fire and explosion protection: Do not heat above flash point.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Store containers closed and protect against rain, dust, heat and other atmospheric influences.

- · Storage class: 10
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3/8h (worker)	
	DNEL/general population/Local effects/Long-term	1.2 mg/m3/24h (consumer)	
64742-55-	8 Distillates (petroleum), hydrotreated light par	affinic	
Dermal	DNEL / Workers / Local Effects / Long-term	1 mg/kg/8h (worker)	
Inhalative	DNEL	2.7-5.4 mg/m3/8h (worker)	
	DNEL	1.2 mg/m3/24h (consumer)	
64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic			
Inhalative	DNEL	5.4 mg/m3/8h (worker)	
	DNEL	1.2 mg/m3/24h (consumer)	
64742-56-	9 Distillates (petroleum), solvent-dewaxed light	paraffinic	
Dermal	DNEL / Workers / Systemic Effects / Long-term	1 mg/kg/8h (worker)	
Inhalative	DNEL / Workers / Systemic Effects / Long-term	2.7 mg/m3/8h (worker)	
PNECs			

- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)



Printing date 30.01.2024 Version number 2.3 Revision: 01.02.2022

Trade name: PRISMA ZX SAE 75W/90

(Contd. of page 3)

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

#### · Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

#### Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

## 9 Physical and Chemical Properties

· General Information

· Appearance:

Form: Fluid
Colour: Yellow
Odour: Characteristic
Odour threshold: Not determined.
pH-value: Not determined.

Change in condition

Melting point/freezing point:
Initial boiling point and boiling range: Undetermined.
Flash point:
Flammability (solid, gas):
Auto-ignition temperature:
Decomposition temperature:
Undetermined.
>200 °C
Not applicable.
>260 °C (DIN 51794)
Not determined.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.

• **Density at 20 °C:** 0.873 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

Solubility in / Miscibility with

• water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• **Dynamic:** Not determined.

• **Kinematic:** 87 mm²/s @ 40 °C (DIN 51562-1)

· Other information No further relevant information available.

AU

Revision: 01.02.2022

Version number 2.3 Printing date 30.01.2024

Trade name: PRISMA ZX SAE 75W/90

(Contd. of page 4)

# 10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological Information

- Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	evant for classification:
72623-87-	1 Lubricat	ing oils (petroleum), C20-50, hydrotreated neutral oil-based
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)
64742-55-	8 Distillate	es (petroleum), hydrotreated light paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
64742-65-	0 Distillate	es (petroleum), solvent-dewaxed heavy paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
		(Contd. on page

Revision: 01.02.2022

Printing date 30.01.2024

Version number 2.3

Trade name: PRISMA ZX SAE 75W/90

		(Contd. of page
64742-54-	7 Distillate	es (petroleum), hydrotreated heavy paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
64742-56-	9 Distillate	es (petroleum), solvent-dewaxed light paraffinic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

# 12 Ecological Information

· Toxicity

72623	-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
64742	-55-8 Distillates (petroleum), hydrotreated light paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
	>100 mg/l/96h (Pimephales promelas) (OECD 203)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
	(Contd. on pag

MOTOREX
Oil of Switzerland
Revision: 01.02.2022

Printing date 30.01.2024

Version number 2.3

Trade name: PRISMA ZX SAE 75W/90

		(Contd. of page 6)			
EL50	10,000 mg/l/48h (aquatic invertebrates)	(Conta. or page o)			
NOEL	>100 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201)				
64742	-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic				
LL50	10,000 mg/l/96h (aquatic invertebrates)				
	100 mg/l/96h (fish)				
LL50	10,000 mg/l/72h (aquatic invertebrates)				
LL50	10,000 mg/l/48h (aquatic invertebrates)				
LL50	10,000 mg/l/24h (aquatic invertebrates)				
EL50	10,000 mg/l/48h (aquatic invertebrates)				
64742	-54-7 Distillates (petroleum), hydrotreated heavy paraffinic				
LL50	10,000 mg/l/96h (aquatic invertebrates)				
	100 mg/l/96h (fish)				
LL50	10,000 mg/l/72h (aquatic invertebrates)				
LL50	10,000 mg/l/48h (aquatic invertebrates)				
LL50	10,000 mg/l/24h (aquatic invertebrates)				
EL50	10,000 mg/l/48h (aquatic invertebrates)				
64742	64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic				
LL50	10,000 mg/l/96h (aquatic invertebrates)				
	100 mg/l/96h (fish)				
LL50	10,000 mg/l/72h (aquatic invertebrates)				
LL50	10,000 mg/l/48h (aquatic invertebrates)				
LL50	10,000 mg/l/24h (aquatic invertebrates)				
EL50	10,000 mg/l/48h (aquatic invertebrates)				

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:

#### · Bioaccumulative potential

### 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic

Partition coefficient | >3.5 [---] (log Kow) (Bioaccumulation)

### 64742-65-0 Distillates (petroleum), solvent-dewaxed heavy paraffinic

Partition coefficient >6 [---] (log Kow) (Bioaccumulation)

### 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Partition coefficient >6 [---] (log Kow) (Bioaccumulation)

### 64742-56-9 Distillates (petroleum), solvent-dewaxed light paraffinic

Partition coefficient | >3.5 [---] (log Kow) (Bioaccumulation)

- Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Water hazard class 2 (according to Appendix 1 AWSV): significantly hazardous to water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

#### · PBT:

255881-94-8 Alkyl dithiophosphate

- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

ΑU

MOTOREX Oil of Switzerland
Revision: 01.02.2022

Printing date 30.01.2024

Version number 2.3

Trade name: PRISMA ZX SAE 75W/90

(Contd. of page 7)

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADG, IMDG, IATA	Not classified as hazardous for transport
UN proper shipping name	
ADG, IMDG, IATA	Not classified as hazardous for transport
Transport hazard class(es)	
ADG, ADN, IMDG, IATA	
Class	Not classified as hazardous for transport
Packing group	
ADG, IMDG, IATA	Not classified as hazardous for transport
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Anna	ex II of
Marpol and the IBC Code	Not applicable.

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian In	· Australian Inventory of Industrial Chemicals		
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic		
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic		
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic		
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic		
255881-94-8	Alkyl dithiophosphate		
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic		
	Distillates (petroleum), solvent-refined heavy paraffinic		
8042-47-5	White mineral oil (petroleum)		

(Contd. on page 9)

MOTOREX Oil of Switzerland
Revision: 01.02.2022

Printing date 30.01.2024

Version number 2.3

Trade name: PRISMA ZX SAE 75W/90

		(Contd. of page 8)		
	octylamine			
12645-31-7	Phosphoric acid, 2-ethylhexyl ester			
107-21-1	Ethane-1,2-diol			
Standard for the Uniform Scheduling of Medicines and Poisons				
107-21-1 Ethane-1,2-diol S5, S6, S1		S5, S6, S10		
· Australia: Priority Existing Chemicals				
None of the ingredients is listed.				

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 255881-94-8 Alkyl dithiophosphate
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- · Relevant phrases

H304 May be fatal if swallowed and enters airways. H361 Suspected of damaging fertility or the unborn child.

- · Department issuing SDS: Abteilung Produktsicherheit
- Contact:
- · Abbreviations and acronyms:

Repr. 2: Reproductive toxicity – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

\* Data compared to the previous version altered.

- AU