MOTOREX Oil of Switzerland
Revision: 18.12.2023

Printing date 30.01.2024

Version number 2.2

1 Identification

- · Product identifier
- · Trade name: RACING FORK OIL 2,5W
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Only for proper handling.

Fork oil

- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- · Label elements
- GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labelling:

Distillates (petroleum), hydrotreated light naphthenic

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics

Lubricating oils, C15-30, hydrotreated neutral oil-based

· Hazard statements

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 2)

MOTOREX*
Oil of Switzerland
Revision: 18.12.2023

Printing date 30.01.2024 Version number 2.2

Trade name: RACING FORK OIL 2,5W

(Contd. of page 1)

- Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|--|-------------|
| CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2 | Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304 | 70-90% |
| CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5 | Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Asp. Tox. 1, H304 | ≥2.5-≤7.5% |
| CAS: 64742-46-7 EINECS: 265-148-2 | Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304 | ≥0.25-≤2.5% |

Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and nitrogen oxides can be formed.

· Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

MOTOREX Oil of Switzerland
Revision: 18.12.2023

Printing date 30.01.2024 Version number 2.2

Trade name: RACING FORK OIL 2,5W

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- · Handling:
- Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.

- · Information about fire and explosion protection: Do not heat above flash point.
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

Store containers closed and protect against rain, dust, heat and other atmospheric influences. Keep container tightly sealed.

- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

| · DNELs | | | |
|------------|--|--------------------------|--|
| 64742-53- | 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic | | |
| Inhalative | DNEL / Workers / Local Effects / Long-term | 5.4 mg/m3 (worker) | |
| 72623-87- | 72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | | |
| Inhalative | DNEL / Workers / Local Effects / Long-term | 5.4 mg/m3/8h (worker) | |
| | DNEL/general population/Local effects/Long-term | 1.2 mg/m3/24h (consumer) | |
| 64742-46- | 64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics | | |
| Dermal | DNEL / Workers / Systemic effects / Long-term | 2.9 mg/kg/24h (worker) | |
| Inhalative | DNEL / Workers / Systemic effects / Long-term | 16 mg/m3 (worker) | |

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 4)



Printing date 30.01.2024 Version number 2.2 Revision: 18.12.2023

Trade name: RACING FORK OIL 2,5W

(Contd. of page 3)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information

· Appearance:

· Form: Fluid · Colour: Red

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.
 Initial boiling point and boiling range: Undetermined.
 Flash point: 120 °C

• Flammability (solid, gas):
• Auto-ignition temperature:

Not applicable.

>270 °C (DIN 51794)

• **Decomposition temperature:** Not determined.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.

• Density at 20 °C: 0.881 g/cm³ (ASTM D 4052)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

· water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.
Kinematic: 15.9 mm²/s @ 40 °C

· Solvent separation test:

· **VOC (EC)** 0.05 %

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 5)



Printing date 30.01.2024 Version number 2.2

Trade name: RACING FORK OIL 2,5W

(Contd. of page 4)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 | · LD/LC50 values relevant for classification: | | |
|------------|---|--|--|
| 64742-53- | 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic | | |
| Oral | LD50 | 5,000 mg/kg (rat) | |
| | LOAEL | 125 mg/kg/24h (rat) | |
| Dermal | LD50 | 2,000-5,000 mg/kg (rabbit) | |
| | NOEL | 30-2,000 mg/kg/24h (rat) | |
| | NOAEL | 150 mg/kg/24h (mouse) | |
| | | 1,000 mg/kg/24h (rabbit) | |
| | LOAEL | 100 mg/kg/24h (mouse) | |
| Inhalative | LC50 / 4h | 2.18-5.53 mg/l (rat) | |
| | NOEL | 220 mg/m3 (rat) | |
| | NOAEL | 980 mg/m3 (rat) | |
| 72623-87- | | ing oils (petroleum), C20-50, hydrotreated neutral oil-based | |
| Oral | LD50 | 5,000 mg/kg (rat) | |
| | LOAEL | 125 mg/kg/24h (rat) | |
| Dermal | LD50 | 2,000-5,000 mg/kg (rabbit) | |
| | NOAEL | 150 mg/kg/24h (mouse) | |
| | | 30-2,000 mg/kg/24h (rat) | |
| | | 1,000 mg/kg/24h (rabbit) | |
| | LOAEL | 100 mg/kg/24h (mouse) | |
| Inhalative | LC50 / 4h | 2.18-5.53 mg/l (rat) | |
| | NOAEC | 980 mg/m3 (rat) | |
| | NOEC | 220 mg/m3 (rat) | |
| | | rbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics | |
| Oral | LD50 | 5,000 mg/kg (rat) | |
| Dermal | LD50 | 2,000 mg/kg (rabbit) | |
| | NOAEL | 25-125 mg/kg/24h (rat) | |
| | | 1,000 mg/kg/24h (rabbit) | |
| | LOAEL | 30 mg/kg/24h (rat) | |
| Inhalative | | 1.72-4.6 mg/l (rat) | |
| | NOAEC | 880-1,710 mg/m3 (rat) | |
| | LOEL | 23-24 mg/m3 (rat) | |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

MOTOREX*
Oil of Switzerland
Revision: 18.12.2023

Printing date 30.01.2024

Version number 2.2

Trade name: RACING FORK OIL 2,5W

(Contd. of page 5)

· Aspiration hazard May be fatal if swallowed and enters airways.

12 Ecological Information

- Toxicity

| · I OXIC | · loxicity | | |
|----------|--|--|--|
| · Aqua | tic toxicity: | | |
| 64742 | 2-53-6 Distillates (petroleum), hydrotreated light naphthenic | | |
| LL50 | 10,000 mg/l/96h (aquatic invertebrates) | | |
| | 100 mg/l/96h (fish) | | |
| LL50 | 10,000 mg/l/72h (aquatic invertebrates) | | |
| LL50 | 10,000 mg/l/48h (aquatic invertebrates) | | |
| LL50 | 10,000 mg/l/24h (aquatic invertebrates) | | |
| EL50 | 10,000 mg/l/48h (aquatic invertebrates) | | |
| 72623 | 3-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | | |
| LL50 | 10,000 mg/l/96h (aquatic invertebrates) | | |
| | 100 mg/l/96h (fish) | | |
| LL50 | 10,000 mg/l/72h (aquatic invertebrates) | | |
| LL50 | 10,000 mg/l/48h (aquatic invertebrates) | | |
| LL50 | 10,000 mg/l/24h (aquatic invertebrates) | | |
| EL50 | 10,000 mg/l/48h (aquatic invertebrates) | | |
| 64742 | 2-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics | | |
| LL50 | 1.13-65 mg/l/96h (fish) | | |
| LL50 | 21-150 mg/l/72h (fish) | | |
| LL50 | 28-180 mg/l/48h (fish) | | |
| LL50 | 100-1,000 mg/l/24h (fish) | | |
| EL50 | 7.385-210 mg/l/48h (aquatic invertebrates) | | |
| EL50 | 180-1,000 mg/l/24h (aquatic invertebrates) | | |
| EL50 | 1.714-22 mg/l/72h (algae / cyanobacteria) | | |

- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:

· Bioaccumulative potential

64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

Partition coefficient 2-6 [---] (log Kow) (Bioaccumulation)

64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics

Biodegradability 74 % (28d) (Biodegradability) (OECD 306)

- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

AU

MOTOREX Oil of Switzerland
Revision: 18.12.2023

Printing date 30.01.2024 Version number 2.2

Trade name: RACING FORK OIL 2,5W

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

| Transport information | |
|--|---|
| UN-Number ADG, ADN, IMDG, IATA | Not classified as hazardous for transport |
| · UN proper shipping name · ADG, ADN, IMDG, IATA | Not classified as hazardous for transport |
| Transport hazard class(es) | |
| · ADG, ADN, IMDG, IATA · Class | Not classified as hazardous for transport |
| Packing group ADG, IMDG, IATA | Not classified as hazardous for transport |
| Environmental hazards: Marine pollutant: | No |
| Special precautions for user | Not applicable. |
| Transport in bulk according to Anno Marpol and the IBC Code | ex II of Not applicable. |
| UN "Model Regulation": | Not classified as hazardous for transport |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

| - Australian I | · Australian Inventory of Industrial Chemicals | |
|----------------|---|--|
| 64742-53-6 | Distillates (petroleum), hydrotreated light naphthenic | |
| 64742-57-0 | Residual oils (petroleum), hydrotreated | |
| 72623-87-1 | Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | |
| 64742-46-7 | Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics | |
| 72623-86-0 | Lubricating oils, C15-30, hydrotreated neutral oil-based | |
| 97-88-1 | n-butyl methacrylate | |
| 64742-53-6 | Distillates (petroleum), hydrotreated light naphthenic | |
| 64742-55-8 | Distillates (petroleum), hydrotreated light paraffinic | |
| 72623-86-0 | Lubricating oils, C15-30, hydrotreated neutral oil-based | |
| | Bis(2-ethylhexyl)maleat | |
| 25307-17-9 | 2,2'-(9-octadecenylimino)bisethanol | |

(Contd. on page 8)

MOTOREX Oil of Switzerland
Revision: 18.12.2023

Printing date 30.01.2024

Version number 2.2

Trade name: RACING FORK OIL 2,5W

| | (Contd. of page 7) |
|--|--|
| 1330-20-7 | xylene |
| 100-41-4 | ethylbenzene |
| | ethyl acrylate |
| 556-67-2 | octamethylcyclotetrasiloxane |
| · Standard fo | or the Uniform Scheduling of Medicines and Poisons |
| 1330-20-7 | xylene S6 |
| · Australia: Priority Existing Chemicals | |
| None of the ingredients is listed. | |

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

- · purity requirement
- Relevant phrases

H304 May be fatal if swallowed and enters airways.

- · Department issuing SDS: Abteilung Produktsicherheit
- Contact:
- · Abbreviations and acronyms:

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

- ΔΙΙ.