MOTOREX*
Oil of Switzerland

Revision: 16.01.2024

Printing date 30.01.2024

Version number 2.2

1 Identification

- · Product identifier
- · Trade name: RACING FORK OIL 5W
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

TVO TUTTICI TCICVAIN IIIIOTTIALIOTT AVAIIADIC.

· Application of the substance / the mixture

Only for proper handling.

Fork oil

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG

Bern-Zürich-Strasse 31, Postfach

CH-4901 Langenthal

Tel. +41 (0)62 919 75 75

www.motorex.com

A1 Accessory Imports

60-62 Burchill St.

Loganholme

4129 QLD

Australia

Phone: 07 3451 1300

- · Further information obtainable from: msds@motorex.com
- · Emergency telephone number:

In case of a medical emergency following exposure to a chemical, call Poisons Information Centre Australia 13 11 26

2 Hazard(s) Identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonised System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	60-80%
CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Asp. Tox. 1, H304	≥2.5-≤7.5%
CAS: 64742-46-7 EINECS: 265-148-2	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304	≥0.25-≤3%

(Contd. on page 2)

MOTOREX*
Oil of Switzerland

Revision: 16.01.2024

Printing date 30.01.2024 Version number 2.2

Trade name: RACING FORK OIL 5W

(Contd. of page 1)

Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

· After eve contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental Release Measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- Handling:
- · Precautions for safe handling No special measures required.
- · Information about fire and explosion protection: No special measures required.
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

The recommended storage temperature is (deg.C): ≤50°C

· Storage class: 10

(Contd. on page 3)

MOTOREX Oil of Switzerland
Revision: 16.01.2024

Printing date 30.01.2024 Version number 2.2

Trade name: RACING FORK OIL 5W

(Contd. of page 2)

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- · Additional information about design of technical facilities: No further data; see section 7.
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs				
64742-53-	6 Distillates (petroleum), hydrotreated light nap	hthenic		
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3 (worker)		
72623-87-	72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based			
Inhalative	DNEL / Workers / Local Effects / Long-term	5.4 mg/m3/8h (worker)		
	DNEL/general population/Local effects/Long-term	1.2 mg/m3/24h (consumer)		
64742-46-	64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics			
Dermal	DNEL / Workers / Systemic effects / Long-term	2.9 mg/kg/24h (worker)		
Inhalative	DNEL / Workers / Systemic effects / Long-term	16 mg/m3 (worker)		

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not determined.

- · Eye protection: Goggles recommended during refilling
- · Body protection: Protective work clothing

9 Physical and Chemical Properties

· General Information · Appearance:

Form: Fluid

Colour: Red
Odour: Characteristic
Odour threshold: Not determined.

Change in condition

· pH-value:

Melting point/freezing point: Undetermined.

(Contd. on page 4)



Printing date 30.01.2024 Version number 2.2 Revision: 16.01.2024

Trade name: RACING FORK OIL 5W

(Contd. of page 3)

· Initial boiling point and boiling range: Undetermined.

· Flash point: 130 °C

Flammability (solid, gas): Not applicable. >270 °C (DIN 51794) · Auto-ignition temperature: Decomposition temperature: Not determined.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

· Lower: Not determined. · Upper: Not determined.

Vapour pressure at 20 °C: 1.6 hPa

Density at 20 °C: 0.885 g/cm3 (ASTM D 4052)

Relative density Not determined. Vapour density Not determined. · Evaporation rate Not determined.

Solubility in / Miscibility with

· water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

· Dynamic: Not determined. · Kinematic: 23.4 mm²/s @ 40 °C

· Solvent separation test:

0.05 % · VOC (EC)

No further relevant information available. · Other information

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	evant for classification:
64742-53-	6 Distillate	es (petroleum), hydrotreated light naphthenic
Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOEL	30-2,000 mg/kg/24h (rat)
	NOAEL	150 mg/kg/24h (mouse)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)
		(Contd. on page 5)

(Contd. on page 5)

Revision: 16.01.2024

Printing date 30.01.2024

Version number 2.2

Trade name: RACING FORK OIL 5W

72622 97	1 Lubricat	(Contd. of page ing oils (petroleum), C20-50, hydrotreated neutral oil-based
0ral	LD50	5,000 mg/kg (rat)
O, a,	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	100 mg/kg/24h (mouse)
Inhalative	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)
64742-46-	7 Hydroca	rbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
	NOAEL	25-125 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
	LOAEL	30 mg/kg/24h (rat)
Inhalative	LC50 / 4h	1.72-4.6 mg/l (rat)
	NOAEC	880-1,710 mg/m3 (rat)
	LOEL	23-24 mg/m3 (rat)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

12 Ecological Information

· Toxicity

· Aqua	tic toxicity:
64742	2-53-6 Distillates (petroleum), hydrotreated light naphthenic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
72623	8-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
	(Contd. on page 6

Revision: 16.01.2024

Printing date 30.01.2024

Version number 2.2

Trade name: RACING FORK OIL 5W

	(Conta. or page 5)	
64742	2-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics	
LL50	1.13-65 mg/l/96h (fish)	
LL50	21-150 mg/l/72h (fish)	
LL50	28-180 mg/l/48h (fish)	
LL50	100-1,000 mg/l/24h (fish)	
EL50	7.385-210 mg/l/48h (aquatic invertebrates)	
EL50	180-1,000 mg/l/24h (aquatic invertebrates)	
EL50	1.714-22 mg/l/72h (algae / cyanobacteria)	

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:

	· · · · · · · · · · · · · · · · · · ·
· Bioaccumulative	potential
64742-53-6 Distilla	ites (petroleum), hydrotreated light naphthenic
Partition coefficient	2-6 [] (log Kow) (Bioaccumulation)
64742-46-7 Hydro	carbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics
Biodegradability	74 % (28d) (Biodegradability) (OECD 306)

- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

Return product and/or partially emptied container in original packaging to the point of sale or hand it over to a collection point for special waste.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADG, ADN, IMDG, IATA	Not classified as hazardous for transport
UN proper shipping name	
ADG, ADN, IMDG, IATA	Not classified as hazardous for transport
Transport hazard class(es)	
ADG, ADN, IMDG, IATA	
Class	Not classified as hazardous for transport

(Contd. on page /

MOTOREX Oil of Switzerland
Revision: 16.01.2024

Printing date 30.01.2024

Version number 2.2

Trade name: RACING FORK OIL 5W

	(Contd. of page
· Packing group · ADG, IMDG, IATA	Not classified as hazardous for transport
· Environmental hazards: · Marine pollutant:	No
Special precautions for user	Not applicable.
· Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
UN "Model Regulation":	Not classified as hazardous for transport

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian	Inventory of Industrial Chemicals	
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
64742-57-0	Residual oils (petroleum), hydrotreated	
72623-87-1	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	
64742-46-7	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics	
72623-86-0	Lubricating oils, C15-30, hydrotreated neutral oil-based	
97-88-1	n-butyl methacrylate	
64742-53-6	Distillates (petroleum), hydrotreated light naphthenic	
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	
72623-86-0	Lubricating oils, C15-30, hydrotreated neutral oil-based	
142-16-5	Bis(2-ethylhexyl)maleat	
<i>25307-17-9</i>	2,2'-(9-octadecenylimino)bisethanol	
29190-28-1	2,4-bis(xylylazo)resorcinol	
1330-20-7	xylene	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
556-67-2	octamethylcyclotetrasiloxane	
· Standard fo	or the Uniform Scheduling of Medicines and Poisons	
1330-20-7	xylene S	S6
Australia I	Priority Existing Chemicals	=

Australia: Priority Existing Chemicals

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

(Contd. on page 8)

MOTOREX*
Oil of Switzerland
Revision: 16.01.2024

Printing date 30.01.2024

Version number 2.2

Trade name: RACING FORK OIL 5W

(Contd. of page 7)

- · purity requirement
- Relevant phrases

H304 May be fatal if swallowed and enters airways.

- · Department issuing SDS: Abteilung Produktsicherheit
- Contact:
- · Abbreviations and acronyms:

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

- ALI